



TSXAMZ600 (45 007 47)

4 inn / 2 ut ana, strøm/sp



Last ned produktdatablad for TSXAMZ600

[Endre dine utvalgskriterier](#) [Produktliste](#)

Finn andre produkter og
tilbehør



Finn ditt Schneider Electric verktøy

[Karakteristikk](#) | [Connections and Schema](#) | [Dokumenter og nedlastning](#)

Teknisk informasjon

 Skjul

Produktspekter	Modicon TSX Micro automation platform
Produkt eller komponent type	Analogue I/O module
Antall kanaler	4 input module 2 output module
Analogue input type	0...10 V 4...20 mA 0...20 mA +/- 10 V
Analogue output type	0...10 V 4...20 mA +/- 10 V 0...20 mA

Komplementær

 Skjul

Analog/digital conversion	11 bits 0...10 V 0...10 V 11 bits 0...20 mA or 4...20 mA 0...20 mA or 4...20 mA 11 bits + sign +/- 10 V +/- 10 V
Measurement resolution	0...20 mA or 4...20 mA 0...10 V or +/- 10 V
Anskaffelsesperioden+H184	16 ms 0...20 mA or 4...20 mA 16 ms 0...10 V or +/- 10 V
Responstid	400 µs +/- 10 V or 0...10 V 400 µs 0...20 mA or 4...20 mA 400 µs +/- 10 V
Utgangslast	<= 0.6 Ohm 0...20 mA or 4...20 mA >= 2 Ohm +/- 10 V or 0...10 V
Beskyttelsestype	Kortslutning +/- 10 V or 0...10 V Kortslutning 0...20 mA or 4...20 mA
Temperature drift	0.107 %/10 °C 0...20 mA or 4...20 mA 0.054 %/10 °C 0...20 mA or 4...20 mA 0.083 %/10 °C +/- 10 V or 0...10 V 0.068 %/10 °C 0...10 V or +/- 10 V
Input impedance	250 Ohm 0...20 mA or 4...20 mA 2.2 Ohm 0...10 V or +/- 10 V
Strømforbruk	180 mA
Isolation voltage	1000 V AC
Vekt	0.24 kg

Bærekraftig

 Skjul

Bærekraftig	Ikke et Green Premium produkt
RoHS (datokode: YYWW)	Compliant - since 0908 - Schneider Electric declaration of conformity