

Home | Product Type | Cabinets, Panels & Enclosures | Closures & Terminals | Fiber Splice & Patch Closures | 760241442 | OFDC-A4-NN/00-NN-N-24





760241442 | OFDC-A4-NN/00-NN-N-24

OFDC-A4 Fiber Optic Splice/Patch Closure, gel cable sealing, 2 pre-installed 12-fiber splice trays, no adapters, no splitter

Available in: Asia | Australia/New Zealand | EMEA | Latin America | No

Specifications View Download ⚠ Share ☑ How to Buy

Support

+ Add to My Products Lists

Features & Benefits	Specifications	Product Support	Documentation & Downloads

Related Products & Accessories Other Ways to Browse

Features and Benefits

- Advanced gel sealing technology ensures fast and easy field handling without a need for special tools
- Individual access to drop cable connection area and seperate zones for looped cable storage for micro-sheet cables only
- Compact and modular design suited for wraparound drop cable installation, enabling faster deployments
- · Allows easy pass-through cabling and integration of optical components, even at later deployment stages

Specifications

Product Classification

Regional Availability	Asia Australia/New Zealand EMEA Latin America North America
Portfolio	CommScope®
Product Type	Single-ended, rectangular fiber closure
Product Series	OFDC


General Specifications

Cable Capacity, Drop	4 Flat 8.0 x 4.5 mm (0.30 x 0.17 in) 4 Round 0-6.0 mm (0-0.23 in) 8 Round 0-4.5 mm (0-0.17 in)
Cable Capacity, Feeder	2 Round 4.5–12.0 mm (0.17–0.47 in)
Cable Sealing Type	Compressed gel
Closure Style	Single-ended
Color	Black
Mounting	Manhole Pedestal Strand Wall
Port Type	No adapter
Splice Tray Included, quantity	2
Splice Tray Type Included	12-way, heat shrink
Splicing Capacity, maximum	24
Splicing Type, Supported	Single fusion

Dimensions

Height	70 mm 2.756 in
Width	94 mm 3.701 in
Length	211 mm 8.307 in
Splice Protector Length, maximum	45 mm 1.772 in
Main Cable Diameter, maximum	12 mm 0.472 in

Ordering Tree



Material Specifications

Material Type Rugged polymer	
------------------------------	--

Environmental Specifications

Installation temperature	-5 °C to +45 °C (+23 °F to +113 °F)
Storage Temperature	-30 °C to +60 °C (-22 °F to +140 °F)
Relative Humidity	93%, non-condensing
Environmental Space	Above ground Below ground
Qualification Standards	IEC 60529, IP68 + 2 m waterhead
UV Resistance	UV stabilized

Packaging and Weights

Packaging quantity	1
Packaging Type	Box Carton
Weight, net	0.55 kg 1.213 lb

Regulatory Compliance/Certifications

Agency	Classification
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
ROHS	Compliant
CHINA-ROHS	Below maximum concentration value
REACH-SVHC	Compliant as per SVHC revision on www.commscope.com/ProductCompliance

Product Support



Customer and Technical Support, Training, Software/Firmware, Repair Services

Documentation & Downloads

Building Information Modeling (BIM) Objects



Revit BIM Models

Installation Instruction
TC-1393-1-SIP-FR OFDC-A4 (French)
TC-1393-IP OFDC-A4 SPLICE/PATCH
TECP-96-194 Cleaning Fiber Connectors and Adapters
Product Compliance Documentation
Statement of Compliance RoHS/REACH
Product Selection Guide
Outdoor Fiber Distribution Closures
Product Specification
760241442 Product specifications
Video
OFDC A4
Visio Stencil
& Visio Stencil Resources
Warranty
CommScope Limited Product Warranty
Related Products and Accessories

Splitters, Combiners & Multiplexers

Related Products



Other Ways to Browse

Browse by Category



Fiber Splice & Patch Closures

Get Help	Company	Quick Links	Featured Brands
Consumers Contact Us How to buy	ontact Us Blog	My CommScope Partners Partner Locator Sales Locator Podcasts	ERA® HELIAX® NOVUX™ ONECELL® RUCKUS®
	Management Team Press Releases	Training Webinars	SURFBOARD® SYSTIMAX®











© 2021 All Rights Reserved

\ccessibility

Supplier Responsibility

Ethics

Privacy & Cookies

Do Not Sell My Information

_

?CP?13053344?-1