



03031 (24 030 11)

MONT.PLATE NS100-250 HOR. M/DREIEH. G



[Last ned produktdatablad for 03031](#)



[Endre dine utvalgskriterier](#) [Produktliste](#)

[Finn andre produkter og tilbehør](#)



[Finn ditt Schneider Electric verktøy](#)

[Karakteristikk](#) | [Dokumenter og nedlastning](#)

Teknisk informasjon

[Skjul](#)

Serie	Prisma
Kompatibel med	Prisma G
Produkt eller komponent type	Montasjeplate
Tilbehør / separat del kategori	Installasjonstilbehør
Installert utstyr	Compact: fast NSX100...160 uten earth leakage protection - control: direct front rotary handle - horisontal installasjon Compact: fast NSX250 uten earth leakage protection - control: direct front rotary handle - horisontal installasjon Easypact: fast CVS100...160 uten earth leakage protection - control: direct front rotary handle - horisontal installasjon Easypact: fast CVS250 uten earth leakage protection - control: direct front rotary handle - horisontal installasjon Compact: fast NSX100...160 med earth leakage protection - control: direct front rotary handle - horisontal installasjon Compact: fast NSX250 med earth leakage protection - control: direct front rotary handle - horisontal installasjon Easypact: fast CVS100...160 med earth leakage protection - control: direct front rotary handle - horisontal installasjon Easypact: fast CVS250 med earth leakage protection - control: direct front rotary handle - horisontal installasjon
Polene beskrivelse	1 x 3P: fast: NSX100...160 horisontal installasjon 1 x 4P: fast: NSX100...160 horisontal installasjon 1 x 3P: fast: NSX250 horisontal installasjon 1 x 4P: fast: NSX250 horisontal installasjon 1 x 4P: fast: CVS100...160 horisontal installasjon 1 x 3P: fast: CVS100...160 horisontal installasjon 1 x 4P: fast: CVS250 horisontal installasjon 1 x 3P: fast: CVS250 horisontal installasjon

Komplementær

[Skjul](#)

Skap/kapsling beskrivelse	Floor-standing enclosure - width 600 mm Wall-mounted enclosure - width 600 mm Floor-standing enclosure - width 850 mm Floor-standing enclosure + duct - width 600 + 300 mm Wall-mounted enclosure + duct - width 600 + 300 mm
Antallet vertikale moduler (50 mm)	5 module(s) : CVS100...160 without earth leakage protection , direct with long terminal shield in 600 mm Wide floor-standing enclosure (cable coming from top or bottom of enclosure) 5 module(s) : CVS100...160 without earth leakage protection , direct with long terminal shield in 600 mm Wide wall-mounted enclosure (cable coming from top or bottom of enclosure) 4 module(s) : CVS100...160 without earth leakage protection , direct with long terminal shield in 600 + 300 mm Wide floor-standing enclosure + duct (cable coming from top or bottom of enclosure) 4 module(s) : CVS100...160 without earth leakage protection , direct with long terminal shield in 600 + 300 mm Wide wall-mounted enclosure + duct (cable coming from top or bottom of enclosure) 4 module(s) : CVS100...160 without earth leakage protection , direct with long terminal shield in 850 mm Wide floor-standing enclosure (cable coming from top or bottom of enclosure) 5 module(s) : CVS250 without earth leakage protection , direct with long terminal shield in 600 mm Wide floor-standing enclosure (cable coming from top or bottom of enclosure) 5 module(s) : CVS250 without earth leakage protection , direct with long terminal shield in 600 mm Wide wall-mounted enclosure (cable coming from top or bottom of enclosure) 4 module(s) : CVS250 without earth leakage protection , direct with long terminal shield in 600 + 300 mm Wide floor-standing enclosure + duct (cable coming from top or bottom of enclosure) 4 module(s) : CVS250 without earth leakage protection , direct with long terminal shield in 600 + 300 mm Wide wall-mounted enclosure + duct (cable coming from top or bottom of enclosure) 4 module(s) : CVS250 without earth leakage protection , direct with long terminal shield in 850 mm Wide floor-standing enclosure (cable coming from top or bottom of enclosure) 4 module(s) : NSX100...160 without earth leakage protection , direct with long terminal shield in 600 + 300 mm Wide floor-standing

[illegible]

	terminal shield in 600 mm Wide wall-mounted enclosure (cable coming from top or bottom of enclosure) 4 module(s) : NSX250 with earth leakage protection , direct with long terminal shield in 850 mm Wide floor-standing enclosure (cable coming from top or bottom of enclosure)
Betingelse for bruken	Need additional plate (2M high) when installation of device is in horizontal
Høyde	150 mm
Vekt	1.08 kg
Type overflate	Matt Glatt
Overflatebeskyttelse	Elektroforese behandling og hot-polymerisert polyester epoxy pulver
Farge	Hvit RAL 9001

Miljø  Skjul	
Standarder	IEC 61439-2
Produktsertifikater	ASEFA

Bærekraftig  Skjul	
Bærekraftig	Green Premium produkt
RoHS (datokode: YYWW)	Compliant - since 0807 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Produktets miljøprofil	Tilgjengelig
Destruksjons-instruks	Krever ingen spesiell avfallshåndtering