



Type Designation	4703
Designation IEC	LR03
System	Zn-MnO ₂ (Alkaline)
Shelf Life (Coding)*	10 years
Nominal Voltage [V]	1.5
Typical Capacity C [mAh]	1260 (discharge with high-resistance)
Permissible Temperature Range	- 20 °C ... 50 °C
Weight, approx. [g]	11
Volume [ccm]	3.8

Dimensions [mm]	min:	max:
Ø	9.5	10.5
A	-	44.5
B	43.3	-
C	4.3	-
E	-	0.5
F	-	3.8
G	0.8	-

Typical Capacities (at 20°C):



Discharge Type	Load	End Voltage[V]	0.9
1H/D, 7D/W	100 mA	Time [h]	10,0
Digital audio		Capacity [mAh]	1079
		Energy [mWh]	1302
Discharge Type	Load	End Voltage[V]	0.9
10S/M, 1H/D, 7D/W	600 mA	Pulse [n]	430
Photo Flash		Capacity [mAh]	720
		Energy [mWh]	792
Discharge Type	Load	End Voltage[V]	0.9
4M/H, 8H/D, 7D/W	5.1 Ω	Time [m]	263
Portable Lighting		Capacity [mAh]	1017
		Energy [mWh]	1214

No publication or circulation of data to third parties without consent of VARTA Consumer Batteries

* In consideration of typical loss of capacity at storage and application.