



Teknisk informasjon

Produktspektre	Altivar Process ATV900
Produkt eller type komponent	Frekvensomformer
Applikasjon	Industriell bruk
Kortnavn utstyr	ATV930
Variant	Med bremseklosser Standard versjon
Produsert i	Asynkrone motorer Synchronous motors
EMC filter	Integrt med 25 m i samsvar med EN/IEC 61800-3 kategori C3
IP-grad	IP00 conforming to IEC 61800-5-1 IP00 conforming to IEC 60529 IP20 i samsvar med IEC 61800-5-1 with kit VW3A9706 IP20 i samsvar med IEC 60529 with kit VW3A9706
Kjølemetode	Tvangsstyrte konveksjon
Nettfrekvens	50...60 Hz +/- 5 %
Network number of phases	3 phases
[Us] matespenning	500...690 V - 15...10 %
Motoreffekt kW	30 KW på 500 V (normal duty) 22 KW på 500 V (heavy duty) 37 KW på 690 V (normal duty) 30 kW på 690 V (heavy duty)
Motoreffekt hk	40 Hp på 500 V normal duty 30 Hp på 500 V heavy duty 50 Hp på 690 V normal duty 40 hp på 690 V heavy duty
Nettstrøm	47,2 A på 500 V (normal duty) 46,2 A på 690 V (normal duty) 37,7 A på 500 V (heavy duty) 38,5 A på 690 V (heavy duty)
Maks kortslutningsnivå Isc	70 kA
Tilsynelatende effekt	55,2 KVA på 690 V (normal duty) 46 kVA på 690 V (heavy duty)
Nominell utgangsstrøm	34 A på 2,5 kHz for heavy duty 45 A på 2,5 kHz for normal duty
Maksimale transient strøm	51 A under 60 s (heavy duty) 54 A under 60 s (normal duty)
Motorkontroll metode	Variabelt dreiemoment standard Optimalisert dreiemoment-modus Konstant dreiemoment standard
Synchronous motor control profile	Permanent magnet motor Synchronous reluctance motor
Speed drive utgangsfrekvens	0,1...599 Hz
Nominell svitsjefrekvens	2,5 kHz
Switching frequency	1...4,9 kHz Justbar 2,5...4,9 kHz med belastningsfaktor
Sikkerhetsfunksjon	STO (safe torque off) SIL 3
Number of preset speeds	16 forhåndsinnstilte hastigheter

Kommunikasjonsprotokoll	Modbus serial Modbus TCP EtherNet/IP
Option module	Slot A: communication module for Profibus DP V1 Slot A: communication module for Profinet Slot A: communication module for DeviceNet Slot A: communication module for EtherCAT Slot A: communication module for CANopen daisy chain RJ45 Slot A: communication module for CANopen SUB-D 9 Slot A: communication module for CANopen screw terminals Slot A/slot B/slot C: digital and analog I/O extension module Slot A/slot B/slot C: output relay extension module Slot B: 5/12 V digital encoder interface module Slot B: analog encoder interface module Slot B: resolver encoder interface module Communication module for Ethernet Powerlink

Komplementær

Utgangsspenning	<= strømforsyningsspenning
Motor slip kompensasjon	Automatic whatever the load Can be suppressed Justrbar Not available in permanent magnet motor law
Akselerasjons- og retardasjonsramper	S, U eller tilpasset Linear adjustable separately from 0.01...9999 s
Bremsing til stillstand	Ved DC-bremsing
Beskyttelsestype	Thermal protection: motor Safe torque off: motor Motor phase break: motor Thermal protection: drive Safe torque off: drive Overheating: drive Overcurrent between output phases and earth: drive Overload of output voltage: drive Short-circuit protection: drive Motor phase break: drive Overvoltages on the DC bus: drive Line supply overvoltage: drive Line supply undervoltage: drive Line supply phase loss: drive Overspeed: drive Break on the control circuit: drive
Frekvensoppløsning	Display unit: 0.1 Hz Analog input: 0.012/50 Hz
Elektrisk tilkobling	Control: screw terminal 0.5...1.5 mm ² /AWG 20...AWG 16 Line side: screw terminal 16...50 mm ² /AWG 6...AWG 1 Motor: screw terminal 16...50 mm ² /AWG 6...AWG 1 DC bus: screw terminal 16...50 mm ² /AWG 6...AWG 1
Type konnektør	2 RJ45 for Ethernet IP/Modbus TCP on the control block 1 RJ45 for Modbus serial on the control block
Fysisk interface	2-wire RS 485 for Modbus serial
Ramme for overføring	RTU for Modbus serial
Transmission rate	10/100 Mbit/s for Ethernet IP/Modbus TCP 4.8, 9.6, 19.2, 38.4 kbit/s for Modbus serial
Exchange-modus	Half duplex, full duplex, autonegotiation Ethernet IP/Modbus TCP
Datoformat	8 bits, configurable odd, even or no parity for Modbus serial
Polarisasjonstype	No impedance for Modbus serial
Antall adresser	1...247 for Modbus serial
Tilgangsmetode	Slave Modbus TCP
Supply	External supply for digital inputs: 24 V DC (19...30 V), <1.25 mA, protection type: overload and short-circuit protection Internal supply for reference potentiometer (1 to 10 kOhm): 10.5 V DC +/- 5 %, <10 mA, protection type: overload and short-circuit protection Internal supply for digital inputs and STO: 24 V DC (21...27 V), <200 mA, protection type: overload and short-circuit protection

Lokal varsling	Local diagnostic: 3 LED (mono/dual colour) Presence of voltage: 1 LED (red) Embedded communication status: 3 LED (dual colour) Communication module status: 4 LED (dual colour)
Bredde	331 mm
Høyde	630 mm
Dybde	297 mm
Vekt	53 kg
Antall analoge innganger	3
Analogue input type	AI1, AI2, AI3 software-configurable voltage: 0...10 V DC, impedance: 30 kOhm, resolution 12 bits AI1, AI2, AI3 software-configurable current: 0...20 mA/4...20 mA, impedance: 250 Ohm, resolution 12 bits
Discrete input number	10
Discrete input type	DI1...DI8 programmable, 24 V DC (<= 30 V), impedance: 3.5 kOhm DI7, DI8 programmable as pulse input: 0...30 kHz, 24 V DC (<= 30 V) STOA, STOB safe torque off, 24 V DC (<= 30 V), impedance: > 2.2 kOhm
Input compatibility	DI1...DI8: discrete input level 1 PLC conforming to EN/IEC 61131-2 DI7, DI8: pulse input level 1 PLC conforming to IEC 65A-68 STOA, STOB: discrete input level 1 PLC conforming to EN/IEC 61131-2
Diskret inngangs logikk	Positive logic (source) (DI1...DI8), < 5 V (state 0), > 11 V (state 1) Negative logic (sink) (DI1...DI8), > 16 V (state 0), < 10 V (state 1) Positive logic (source) (DI7, DI8), < 0.6 V (state 0), > 2.5 V (state 1) Positive logic (source) (STOA, STOB), < 5 V (state 0), > 11 V (state 1)
Analog utgangsnummer	2
Analog utgangstype	Software-configurable voltage AQ1, AQ2: 0...10 V DC impedance 470 Ohm, resolution 10 bits Software-configurable current AQ1, AQ2: 0...20 mA impedance 500 Ohm, resolution 10 bits
Discrete output number	2
Digitale utganger	Logic output DQ+ 0...1 kHz <= 30 V DC 100 mA Programmable as pulse output DQ+ 0...30 kHz <= 30 V DC 20 mA Logic output DQ- 0...1 kHz <= 30 V DC 100 mA
Sampling varighet	2 Ms +/- 0.5 ms (DI1...DI8) - discrete input 5 Ms +/- 1 ms (DI7, DI8) - pulse input 1 Ms +/- 1 ms (AI1, AI2, AI3) - analog input 5 ms +/- 1 ms (AQ1, AQ2) - analog output
Nøyaktighet	+/- 0.6 % AI1, AI2, AI3 for a temperature variation 60 °C analog input +/- 1 % AQ1, AQ2 for a temperature variation 60 °C analog output
Lineær feil	AI1, AI2, AI3: +/- 0.15 % of maximum value for analog input AQ1, AQ2: +/- 0.2 % for analog output
Maximum svitsjestrom	Relay output R1 on resistive load, cos phi = 1: 3 A at 250 V AC Relay output R1 on resistive load, cos phi = 1: 3 A at 30 V DC Relay output R1 on inductive load, cos phi = 0.4 and L/R = 7 ms: 2 A at 250 V AC Relay output R1 on inductive load, cos phi = 0.4 and L/R = 7 ms: 2 A at 30 V DC Relay output R2, R3 on resistive load, cos phi = 1: 5 A at 250 V AC Relay output R2, R3 on resistive load, cos phi = 1: 5 A at 30 V DC Relay output R2, R3 on inductive load, cos phi = 0.4 and L/R = 7 ms: 2 A at 250 V AC Relay output R2, R3 on inductive load, cos phi = 0.4 and L/R = 7 ms: 2 A at 30 V DC
Relé utgang nummer	3
Reléutgangstype	Configurable relay logic R1: fault relay NO/NC electrical durability 100000 cycles Configurable relay logic R2: sequence relay NO electrical durability 1000000 cycles Configurable relay logic R3: sequence relay NO electrical durability 1000000 cycles
Refresh time	Relay output (R1, R2, R3): 5 ms (+/- 0.5 ms)
Minimum brytestrom	Relay output R1, R2, R3: 5 mA at 24 V DC
Skille	Between power and control terminals
Monteringsmetode	Veggmontering

Miljø

Isolasjonsmotstand	> 1 MOhm 500 V DC for 1 minute to earth
Noise level	56 dB conforming to 86/188/EEC
Effekttap i W	Tvangsstyrkt konveksjon: 557 W på 500 V, vekslingsfrekvens 2,5 kHz Naturlig konveksjon: 178 W på 500 V, vekslingsfrekvens 2,5 kHz
Vibrasjonsmotstand	1.5 mm peak to peak (f= 2...13 Hz) conforming to IEC 60068-2-6 1 gn (f= 13...200 Hz) conforming to IEC 60068-2-6
Støtmotstand	15 gn for 11 ms i samsvar med IEC 60068-2-27
Volum av kjøleluft	406 m3/t
Driftsposisjon	Vertikal +/- 10 grader
Elektromagnetisk kompatibilitet	Electrostatic discharge immunity test level 3 conforming to IEC 61000-4-2 Radiated radio-frequency electromagnetic field immunity test level 3 conforming to IEC 61000-4-3 Electrical fast transient/burst immunity test level 4 conforming to IEC 61000-4-4 1.2/50 µs - 8/20 µs surge immunity test level 3 conforming to IEC 61000-4-5 Conducted radio-frequency immunity test level 3 conforming to IEC 61000-4-6
Miljødata	Chemical pollution resistance class 3C3 conforming to EN/IEC 60721-3-3 Dust pollution resistance class 3S3 conforming to EN/IEC 60721-3-3
Forurensninggrad	2 conforming to EN/IEC 61800-5-1
Relativ fuktighet	5...95 % without condensation conforming to IEC 60068-2-3
Omgivelsestemperatur for drift	-15...50 °C (without derating) 50...60 °C (med belastningsfaktor)
Omgivelsestemperatur for lagring	-40...70 °C
Operating altitude	<= 1000 m without derating 1000...4800 m with current derating 1 % per 100 m
Standarder	UL 508C EN/IEC 61800-3 Environment 2 category C3 EN/IEC 61800-3 EN/IEC 61800-5-1 IEC 61000-3-12 IEC 60721-3 IEC 61508 IEC 13849-1
Produktsertifikater	TÜV UL CSA
Merking	CE

Packing Units

Enhetstype forpakning 1	PCE
Antall enheter forpakning 1	1
Forpakning 1 vekt	38 kg
Forpakning 1 høyde	57 cm
Forpakning 1 bredde	43 cm
Forpakning 1 lengde	110 cm

Contractual warranty

Garanti	18 måneder
---------	------------