

@XS-Quad Abonentuttak

- Up to **4 SC adapters**
- Wall mounted, on flush box or DIN rail
- No lid-opening to fix the outlet
- **Ready-to-fix**kit in option

BESKRIVELSE

Optical terminal outlets, installed in the subscriber's home, are the optical equipments materializing the demarcation between the FTTH operator network and the local subscriber's network.

Compact and ergonomic, its design has been studied in **partnership with SismoDesign agency** for a sober, discreet and elegant depiction, to fit at best at the inhabitant.

For security, adapters include an **automatic laser and dust protection**, called « internal shutter ».

The front side contains all the necessary indications (from top to bottom):

- Swiveling flap to protect and hide the identification label
- Area to stick Identification Label (under the flap)
- 4-colour identification code for the adapters
- Indication that polarizing slot is upwards
- Integrated laser symbol

The @XS-Quad outlets range comes in 2 families:

- The “equipped” outlet is provided with adapters and pigtails preinstalled. It must then be connected with the subscriber's cable.
- The “kit” outlet is provided pre-cabled, ready to be fastened without any outlet opening. Cable type and length are customizable.



STANDARDER

Internasjonal
Nexans specification

Nasjonal Orange/
France Telecom



IK
5



Operating temp.
-5 - 45 °C



Watertightness
IP 50



Motstandsdyktighet mot UV
Ja



Brannbeskyttet
UL 94 V0



Static bending rad.
15 mm

Alle tegninger, design, spesifikasjoner, planer og opplysninger om vekt, størrelse og dimensjoner angitt i tekniske eller markedsføringsdokumenter utgitt av eller på vegne av Nexans er kun veiledende og skal ikke være bindende for Nexans eller behandles som en representasjon fra Nexans side.

Generert 22.03.23 www.nexans.no Side 1 / 2

KARAKTERISTIKKER

Konstruksjonsegenskaper

Farge White RAL 9010

Dimensjonsegenskaper

Høyde 80 mm

Bredde 80 mm

Dybde 25 mm

Diameter område 2 - 5 mm

Skjøt nummer 4

Maksimalt antall adapterer 4

Mekaniske egenskaper

IK Rating 5

Bruksegenskaper

Adapter SC/APC

Driftstemperatur område -5 - 45 °C

Watertightness IP 50

Motstandsdyktighet mot UV Ja

Brannbeskyttet UL 94 V0

Min. statisk bøyeradius 15 mm