



Bottom plate, B=1100 mm, UL approved



Powering Business Worldwide™

Part no. BBC-BT-NA
Article no. 107172

Delivery program

| | | | |
|-----------------------|--|----|--|
| Product range | | | 60 mm system |
| Subrange | | | UL bottom plate |
| Material | | | Silicon free, chlorine free |
| Self-extinguishing | | | to UL 94 |
| Temperature resistant | | | to 110°C |
| Description | | | For use when the air gap between the busbars and the mounting plate is not sufficient. |
| Length | | mm | 1100 |
| For use with | | | BBS-3/FL BBS-3/FL-NA BBS-3/PR |

Approvals

| | | | |
|--------------------------------------|--|--|---|
| Product Standards | | | UL508A; CSA-C22.2 No. 14; IEC 60439-1; CE marking |
| UL File No. | | | E300273 |
| UL Category Control No. | | | NMTR, NMTR7 |
| CSA File No. | | | 236217 |
| CSA Class No. | | | 3211-37 |
| North America Certification | | | UL listed, CSA certified |
| Conditions of Acceptability | | | Refer to approbation report |
| Specially designed for North America | | | Yes |
| Suitable for | | | Feeder circuits |
| Current Limiting Circuit-Breaker | | | Refer to approbation report |
| Max. Voltage Rating | | | 600 V AC |
| Degree of Protection | | | Feeder circuits |

Dimensions



