






Conductor connection terminal 1.5-16mm², f. 5mm




Part no. AKU16/5
Article no. 107187

Delivery program


Product range			60 mm system Compact system
Basic function			Connections
Subrange			Universal conductor connection terminals
Description			With integrated retaining spring, open terminal chamber and captive terminal screw
Terminal area W x H		mm	7.5 x 7.5
Width		mm	11.5
Rated operational current	I _e	A	180
Copper strip		mm	1.5 - 16 mm ² AWG 14 - AWG 6.  directly terminated,    8 x 6 x 0.5
For use with			All 5 mm thick flat busbars

Notes

 round conductor, solid


 Flexible, round conductor with correctly crimped ferrule

Round conductor, stranded

 Section conductor, solid

Sector conductor, stranded

 CU band

 CU busbar

Approvals

Product Standards			UL508A; CSA-C22.2 No. 14; IEC 60439-1; CE marking
UL File No.			E307559
UL Category Control No.			NMTR2, NMTR8
CSA File No.			236217
CSA Class No.			3211-37
North America Certification			UL recognized, CSA certified
Conditions of Acceptability			Refer to approbation report
Specially designed for North America			No
Suitable for			Feeder circuits
Current Limiting Circuit-Breaker			Refer to approbation report
Max. Voltage Rating			600 V AC
Degree of Protection			Feeder circuits

Dimensions

