Select your language

- German
- English
- Spanish
- French
- Dutch
- Italian
- Polish
- Czech
- Russian
- Norw egian Bokmål

Worldwide English



DILM820-XHB - Terminal shroud, for DILM750/820



208284 DILM820-XHB

Overview Specifications Resources



208284 DILM820-XHB

Terminal shroud, for DILM750/820
Alternate Catalog No. XTCEXTS820
EL-Nummer (Norway) 4134022
Terminal shroud, For use with: DILM750, DILM820, DILM1000

Delivery program

Design verification as per IEC/EN 61439

- Technical data ETIM 7.0
- Approvals
- Dimensions

Delivery program

Product range

Accessories Accessories

Covers

Description

Terminal shroud

For use with

DILM750

DILM820

DILM1000

For use with

Terminal shroud for DILM580 to DILM820

Instructions

To provide terminals with busbar tag shroud vertical from the front

Design verification as per IEC/EN 61439

Technical data for design verification

Rated operational current for specified heat dissipation [In]

0 A

Heat dissipation per pole, current-dependent [P_{id}]

0 W

Equipment heat dissipation, current-dependent [Pid]

0 W

Static heat dissipation, non-current-dependent [P_{vs}]

0 W

Heat dissipation capacity [P_{diss}]

0 W

Operating ambient temperature min.

-40 °C

Operating ambient temperature max.

+60 °C

IEC/EN 61439 design verification

10.2 Strength of materials and parts 10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.3.2 Verification of resistance of insulating materials to normal heat Weets the product standard's requirements.

10.2 Strength of materials and parts 10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts 10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts 10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of ASSEVBLIES

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9 Insulation properties 10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9 Insulation properties 10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9 Insulation properties 10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

10.10 Temperature rise

Not applicable.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Accessories for low-voltage switch technology (EC002498)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switch technology (accessories) (ecl@ss10.0.1-27-37-13-92 [AKN570013])

Type of accessory

Cover

Approvals

North America Certification
UL/CSA certification not required

Dimensions







CAD uata

- Product-specific CAD data (Web)
- 3D Preview (Web)

DWG files

DA-CD-dilm650_820_xhb File (Web)

Step files

DA-CS-dilm650_820_xhb File (Web)


Additional product information

- Motor starters and "Special Purpose Ratings" for the North American market (PDF)
- Switchgear of Power Factor Correction Systems (PDF)
- X-Start Modern Switching Installations Efficiently Fitted and Wired Securely (PDF)
- Mrror Contacts for Highly-Reliable Information Relating to Safety-Related Control Functions (PDF)
- Effect of the Cabel Capacitance of Long Control Cables on the Actuation of Contactors (PDF)
- Switchgear for Luminaires (PDF)
- Standard Compliant and Functionally Safe Engineering Design with Mechanical Auxiliary Contacts (PDF)
- The Interaction of Contactors with PLCs (PDF)
- Busbar Component Adapters for modern Industrial control panels (PDF)

Explosion drawing




Dimensions single product



Product photo



3D drawing



Instruction Leaflet

 Accessories for Contactors > 170 A (IL03406009Z) Asset (PDF, 01/2021, multilingual)

Standards

• 000Z153 Logo xStart logo

Declaration of Conformity

EU

 Contactor (DA-DC-00003476)
 Asset (PDF)

UK

Contactor (DA-DC-00003825) Asset (PDF)

Download-Center

- Download-Center (this item)
 Eaton EVEA Download-Center download data for this item
- Dow nload-Center
 Eaton EVEA Dow nload-Center

Cenerate data sheet in PDF format
Cenerate data sheet in Excel format

Write a comment Imprint Privacy Policy Legal Disclaimer Terms and Conditions

© 2021 by Eaton Industries GmbH