



Replacement coil, RDC 48: 24 - 48 V DC, AC operation, For use with:
DILM(-C)185, DILM(-C)225, DILM(-C)250

Part no. **DILM250-XSP/E(RDC48)**
 Catalog No. **208250**
 Alternate Catalog No. **XTCERENCOILLTD**
 EL-Nummer (Norway) **4134096**

Delivery program

Actuating voltage		RDC 48: 24 - 48 V DC
Voltage AC/DC		DC operation
For use with		DILM(-C)185 DILM(-C)225 DILM(-C)250

Design verification as per IEC/EN 61439

Technical data for design verification		
Operating ambient temperature min.	°C	-40
Operating ambient temperature max.	°C	60

Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Coil for relay (EC001043)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Contactor (LV) / Reel for contactor (ecl@ss10.0.1-27-37-10-12 [AKF021013])		
Rated control supply voltage Us at AC 50HZ	V	0 - 0
Rated control supply voltage Us at AC 60HZ	V	0 - 0
Rated control supply voltage Us at DC	V	24 - 48
Voltage type for actuating		DC

Approvals

Product Standards		IEC/EN 60947-4-1; UL 508; CSA-C22.2 No. 14-05; CE marking
UL File No.		E29096
UL Category Control No.		NLDX
CSA File No.		1017510
CSA Class No.		3211-04
North America Certification		UL listed, CSA certified
Specially designed for North America		No