



216827  
M22-WRLK-G

Overview

Specifications

Resources



Delivery program

Technical data

Design verification as per IEC/EN 61439

Technical data ETIM 7.0

Approvals

Dimensions

## DELIVERY PROGRAM

Product range  
RMQ-Titan

Basic function  
Illuminated selector switch actuator

Mounting hole diameter [□]  
22.5 mm

Single unit/Complete unit  
Single unit

Design  
With thumb-grip

maintained

**Function:** [□ = spring-return]

□ 60°

2 positions

## Colour

Thumb-grip  
green



Degree of Protection  
IP66

Front ring  
Bezel: titanium

Connection to SmartWire-DT  
yes  
with SWD-RMQ connections

## Instructions

Stay-put/spring-return function, can be changed  
with coding parts M22-XC-Y

# TECHNICAL DATA

## General

Standards  
IEC/EN 60947  
VDE 0660

Lifespan, mechanical [Operations]  
> 0.1 x 10<sup>6</sup>

Operating frequency [Operations/h]  
□ 2000

Operating torque

□ 0.3 Nm

Climatic proofing

Damp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30

Degree of Protection

IP66

Ambient temperature

Open

-25 - +70 °C

Mounting position

As required

Mechanical shock resistance

30

Shock duration 11 ms

Sinusoidal

according to IEC 60068-2-27 g

shipping classification

DNV

GL

LR



Germanischer Lloyd



## DESIGN VERIFICATION AS PER IEC/EN 61439

### Technical data for design verification

Rated operational current for specified heat dissipation [ $I_r$ ]

0 A

Heat dissipation per pole, current-dependent [ $P_{vid}$ ]

0 W

Equipment heat dissipation, current-dependent

[ $P_{vid}$ ]

0 W

Static heat dissipation, non-current-dependent [ $P_{vs}$ ]

0 W

Heat dissipation capacity [ $P_{diss}$ ]

0 W

Operating ambient temperature min.

-25 °C

Operating ambient temperature max.

+70 °C

## IEC/EN 61439 design verification

10.2 Strength of materials and parts

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2 Strength of materials and parts

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2 Strength of materials and parts

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2 Strength of materials and parts

10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects

Meets the product standard's requirements.

10.2 Strength of materials and parts

10.2.4 Resistance to ultra-violet (UV) radiation

Please enquire

10.2 Strength of materials and parts

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts  
10.2.6 Mechanical impact  
Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts  
10.2.7 Inscriptions  
Meets the product standard's requirements.

10.3 Degree of protection of ASSEMBLIES  
Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances  
Meets the product standard's requirements.

10.5 Protection against electric shock  
Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components  
Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections  
Is the panel builder's responsibility.

10.8 Connections for external conductors  
Is the panel builder's responsibility.

10.9 Insulation properties  
10.9.2 Power-frequency electric strength  
Is the panel builder's responsibility.

10.9 Insulation properties  
10.9.3 Impulse withstand voltage  
Is the panel builder's responsibility.

10.9 Insulation properties  
10.9.4 Testing of enclosures made of insulating material  
Is the panel builder's responsibility.

10.10 Temperature rise  
Not applicable.

10.11 Short-circuit rating  
Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility  
Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function  
The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## TECHNICAL DATA ETIM 7.0

Low-voltage industrial components (EG000017) / Front element for selector switch (EC000222)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Front element for selector switches (ecl@ss10.0.1-27-37-12-13 [AKF031014])

Number of switch positions  
2

Type of control element  
Toggle

Suitable for illumination  
Yes

Colour control element  
Black

Colour indicator light cap  
Green

Construction type lens  
Round

Hole diameter  
22.5 mm

Width opening  
0 mm

Height opening  
0 mm

Switching function latching  
Yes

Spring-return  
No

With front ring  
Yes

Material front ring  
Plastic

Colour front ring  
Other

Degree of protection (IP), front side  
IP66

Degree of protection (NEMA)  
4X

## APPROVALS

Product Standards  
IEC/EN 60947-5; UL 508; CSA-C22.2 No. 14-05;  
CSA-C22.2 No. 94-91; CE marking

UL File No.  
E29184

UL Category Control No.  
NKCR



CSA File No.  
012528

CSA Class No.  
3211-03

North America Certification  
UL listed, CSA certified

Degree of Protection  
UL/CSA Type 3R, 4X, 12, 13

## DIMENSIONS







[Imprint](#) | [Privacy Policy](#) | [Legal Disclaimer](#) | [Terms and Conditions](#)  
© 2021 by Eaton Industries GmbH