



## Effektbryter NZM 2 Motorvern 3-polet: NZMN2-...

Effektbryter Ir: 70 -140 A li: 140-1960 A  
NZMN2-ME140 - 4358903



### Tilleggsutstyr:



NZM2-XDV

4358773




NZM2-XTVD

4358774




NZM2-XTVDVR

4358775




NZM1/2-XV4

4358731



M22-K01

4355364




M22-K10

4355363

NZM2/3-XHIV

4358870



NZM2/3-XU208-240

4358767

### Tekniskinformasjon:

$I_k \text{ max: } I_{cs} = I_{cu} = 85 \text{ kA (230V)}$

$I_2: 1,3 \times I_n$

$I_i$ : Se beskrivelse

Rammeklemme for Cu

Komplett effektbryter, 32 ...250 A

Maks: 690 V 50/60 Hz. EN 60947

$I_2$  = høyeste prøvestrøm

$I_i$  = elektromagnetisk utløserstrøm

$I_{sd}$  = forsinket el.magn. utløserstrøm

A-type = termisk/elektromagn. vern

VE-type = elektronisk forsinket vern

ME-type = elektronisk fors. motorvern

Rammeklemme Cu Moment 14Nm

Tunnelklemme Al/Cu Momenet 31Nm

