



Memory card for XC100/200 and XV100

Part no. XT-MEM-MM32M
Article no. 262731

Delivery program

Accessories			Memory cards
			For storage of programs, data, recipes
Description			256 MByte
For use with			MFD4 XC100 XC200 XC121
Information relevant for export to North America			
Product Standards IEC: see Technical Data; UL508; CSA-C22.2 No. 0-M; CSA-C22.2 No. 142-M; CE marking			
UL File No. E135462			
UL Category Control No. NRAQ			
CSA File No. 012528			
CSA Class No. 2252-01			
North America Certification UL listed, CSA certified			
Degree of Protection IEC: IP20, UL/CSA Type: -			

Design verification as per IEC/EN 61439

Technical data for design verification			
Operating ambient temperature min.		°C	0
Operating ambient temperature max.		°C	55

Technical data ETIM 6.0

PLC's (EG000024) / PLC memory card (EC000192)			
Electric engineering, automation, process control engineering / Control / Programmable logic control (SPS) / SPS memory unit (ecl@ss8.1-27-24-22-12 [AKE535011])			
Type of memory			-
Memory size		kByte	32000

Approvals

Product Standards			IEC: see Technical Data; UL508; CSA-C22.2 No. 0-M; CSA-C22.2 No. 142-M; CE marking
UL File No.			E135462
UL Category Control No.			NRAQ
CSA File No.			012528
CSA Class No.			2252-01
North America Certification			UL listed, CSA certified
Specially designed for North America			No
Current Limiting Circuit-Breaker			No
Degree of Protection			IEC: IP20, UL/CSA Type: -