



Wireless Dimming 55mm, preconfigured

Part no. CPAD-00/213
Article no. Y7-193728
Catalog No. 193728

Delivery program

Product Type			Packaged Units Actuator Pushbutton
Mounting type			Flush mounted Surface mounted
Power supply			Battery Mains
Actuation Function			Dimming
Pushbutton compatibility			55 mm (Universal)
Rocker Pitch			1-gang
Color			Pure White

Technical data ETIM 6.0

Installation bus systems (EG000032) / Dimming actuator for bus system (EC001094)			
Electric engineering, automation, process control engineering / Electrical installation, device / Bus system / Bus system dimming actuator (ecl@ss8.1-27-14-31-23 [AKE291012])			
Bus system KNX			No
Bus system KNX radio			No
Bus system radio frequent			Yes
Bus system LON			No
Bus system Powernet			No
Other bus systems			Other
Radio frequent bidirectional			Yes
Model			Dimming actuator
Mounting method			Flush mounted (plaster)
Width in number of modular spacings			3
Bus connection included			Yes
Bus module detachable			No
Substation input			No
Local operation/hand operation			No
With LED indication			Yes
Number of outputs			1
Output power		W	0 - 250
Power boost suitable			No
Type of load			Universal and LED Retrofit
Max. control current		mA	0
Voltage		V	196 - 253
Parallel-service possible			No
Frequency		Hz	50 - 50
Degree of protection (IP)			IP20

Additional product information (links)

(IL019193ZU)CPAD	
(IL019193ZU)CPAD	ftp://ftp.moeller.net/DOCUMENTATION/AWA_INSTRUCTIONS/MA136211191_2018_01.pdf