

Reference Datasheet

Eaton FlexPDU

Pulsar Series



Product	Ref	Description
Eaton FlexPDU	FR : 68435 DIN : 68436 BS : 68437 IEC : 68438	Rackable PDU, flexible mounting (1U or zéro U, or on UPS with RT form factor), 8 FR/DIN outlets or 6 BS or 12 IEC 10A, 1 IEC 16A outlet for cascading, retaining clips on IEC outlets

Packaging	Dimensions (WxDxH*, mm)	Weight (kg)	Nb of products / carton	Barcode (EAN13)
Individual carton	448 x 58 x 180	1.8 kg	1 product / carton	FR : 3553340684357 DIN : 3553340684364 BS : 3553340684371 IEC : 3553340684388
Shipping pallet	1000 x 1200 x 1080	324 kg	180 cartons / pallet	

Packaging content
1 Eaton FlexPDU, 1 IEC 16A/IEC 16A power cord+ 1 IEC 16A/IEC 10A power cord, brackets for 19" mounting or on UPSs with RT form factor

Technical specifications	
Dimensions (H x W x D*)/Weight	44 x 483 x 80 mm / 1,2 kg
Warranty	2 years – Optional 3 years warranty with Warranty+ (according country)
Standards and certifications	FR models : IEC 60884-1 DIN models : DIN 49440-1, DIN 49440-5, DIN49440-6 BS models : BS 1363 IEC models : IEC/EN 60320-1 CE, UL

Options	References
Warranty + (3 years warranty)	66813

*H x W x D = Height x Width x Depth

Reference Datasheet

Eaton HotSwap MBP

Pulsar Series



Product	Ref	Description
Eaton HotSwap MBP	FR : 68430 DIN : 68431 BS : 68432 IEC : 68433 HW : 68434	External universal Bypass module for UPSs up to 3kVA, rackable in 1,5U or zero U, 4 FR/DIN outlets or 3 BS or 6 IEC 10A or terminal blocks (HW=Hard-Wired), 1 IEC 16A for cascading, can be mounted as well on UPS with RT form factor, retaining clips on IEC outlets

Packaging	Dimensions (WxDxH*, mm)	Weight (kg)	Nb of products / carton	Barcode (EAN13)
Individual carton	448 x 58 x 180	1.8 kg	1 product / carton	FR : 3553340684302 DIN : 3553340684319 BS : 3553340684326 IEC : 3553340684333 HW : 3553340684340
Shipping pallet	1000 x 1200 x 1080	324 kg	180 cartons / pallet	

Packaging content
1 Eaton HotSwap MBP, 2 IEC 16A/IEC 16A power cords, brackets for 19" mounting or on UPSs with RT form factor

Technical specifications	
Dimensions (H x W x D*)/Weight	52 x 483 x 120 mm / 1,5 kg
Warranty	2 years – Optional 3 years warranty with Warranty+ (according country)
Standards and certifications	FR models : IEC 60884-1 DIN models : DIN 49440-1, DIN 49440-5, DIN 49440-6 BS models: BS 1363 IEC models : IEC/EN 60320-1 HW models: IEC 60950, EN 50091

Options	Reference
10A FR/DIN power cords for HotSwap MBP (for use with UPSs <2,2 kVA not fitted with IEC16A outlets)	68439
10A BS power cords for HotSwap MBP (for use with UPSs <2,2 kVA not fitted with IEC16A outlets)	68440
Warranty + (3 years warranty)	66813

*H x W x D = Height x Width x Depth