




Auxiliary contact module, 2 pole, 1 N/O, 1 NC, Screw terminals

Part no. **DILMT95-XHI11-SR**
 Catalog No. **190974**

Delivery program

Accessories				Auxiliary contact modules
Function				for standard applications
Number of poles				2 pole
Connection technique				Screw terminals
Rated operational current				
Conventional free air thermal current, 1 pole				
Open				
at 60 °C	I_{th}	A	10	
AC-15				
220 V 230 V 240 V	I_e	A	4	
380 V 400 V 415 V	I_e	A	1.9	
Contacts				
N/O = Normally open				1 N/O
N/C = Normally closed				1 NC
Mounting type				Side mounted
Contact sequence				
For use with				DILMT40... DILMT50... DILMT65... DILMT80... DILMT95...
Type				Side-mounting auxiliary contacts

Technical data

General				
Standards				IEC/EN 60947
Climatic proofing				Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30
Ambient temperature				
Open		°C	-25 - +55	
Ambient temperature, storage		°C	-40 - 80	
Terminal capacities				
Screw terminals				
Solid		mm ²	0.75 - 2.5	
Flexible with ferrule		mm ²	0.75 - 2.5	
Pozidriv screwdriver		Size	2	
Max. tightening torque		Nm	1.2	

Contacts				
Rated operational current				
Conventional free air thermal current, 1 pole				
at 60 °C	I_{th}	A	10	

AC-15			
220 V 230 V 240 V	I _e	A	4
380 V 400 V 415 V	I _e	A	1.9

Design verification as per IEC/EN 61439

Technical data for design verification			
Operating ambient temperature min.		°C	-25
Operating ambient temperature max.		°C	55

Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Auxiliary contact block (EC000041)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Auxiliary switch block (ecL@ss10.0.1-27-37-13-02 [AKN342013])

Number of contacts as change-over contact			0
Number of contacts as normally open contact			1
Number of contacts as normally closed contact			1
Number of fault-signal switches			0
Rated operation current I _e at AC-15, 230 V		A	4
Type of electric connection			Screw connection
Model			Top mounting
Mounting method			Side mounting
Lamp holder			None

Approvals

Specially designed for North America			No
--------------------------------------	--	--	----

Dimensions

