



## Insulated ferrule

**Part no.** ISH2,8  
**Article no.** 090267  
**Catalog No.** ISH2P8

### Delivery program

|                            |  |  |  |
|----------------------------|--|--|--|
| Product range              |  |  | RMQ16 (drilling dimensions 16 mm)  |
| Basic function             |  |  | Accessories  |
| Basic function accessories |  |  | Insulated ferrule  |
| Single unit/Complete unit  |  |  | Single unit  |
|                            |  |  | For fast-on connector 2.8 x 0.8 mm<br>Plug-in from front<br>$U_e > 50 \text{ V AC}$ , $U_e > 120 \text{ V DC}$ |
| Connection to SmartWire-DT |  |  | no   |

### Design verification as per IEC/EN 61439

|  |  |    |     |
|--|--|----|-----|
| Technical data for design verification |  |    |     |
| Operating ambient temperature min.     |  | °C | -25 |
| Operating ambient temperature max.     |  | °C | 60  |

### Technical data ETIM 6.0

|  |  |  |           |
|--|--|--|-----------|
| Low-voltage industrial components (EG000017) / Accessories for low-voltage switch technology (EC002498)  |  |  |           |
| Electric engineering, automation, process control engineering / Low-voltage switch technology / Low-voltage switch technology (accessories) / Component for low-voltage switch technology (accessories) (ec@ss8.1-27-37-92-01 [AKN570010]) |  |  |           |
| Type of accessory  |  |  | Connector |

### Approvals

|                             |  |  |                                   |
|-----------------------------|--|--|-----------------------------------|
| North America Certification |  |  | UL/CSA certification not required |
|-----------------------------|--|--|-----------------------------------|