

**Auxiliary contact, 1N/O+1N/C, 8A, 250V AC**

**Part no. Z-HK**  
**Article no. 248432**



**Delivery program**

Basic function		Accessories for residual current circuit breakers
Basic function accessories		Auxiliary contacts
Application		Switchgear for industrial and advanced commercial applications
Product range		Accessory
Side mounting		for fitting on left to: FI
Contact sequence		

**Design verification as per IEC/EN 61439**

Technical data for design verification		
Operating ambient temperature min.	°C	-5
Operating ambient temperature max.	°C	40

**Technical data ETIM 6.0**

Devices for distribution board-/surface mounting (EG000062) / Auxiliary contact unit for distribution board (EC001286)		
Electric engineering, automation, process control engineering / Electrical installation, device / Breaker switch component / Auxiliary contact unit for distribution board (ecl@ss8.1-27-14-35-02 [AKE327010])		
Device fitting		Earth leakage switch
Additional equipment		Auxiliary switch
Attached at delivery		No
Assembly width (TE)		0.5
Number of normally open contacts		1
Number of normally closed contacts		1
Number of change-over contacts		0
Number of fault-signal switches		0
Rated switch current	A	3
Nominal rated voltage	V	230
Control voltage type		AC
With autotest for earth leakage function		No
Suitable for max. number of poles main contact unit (total)		2
Suitable for max. current main contact unit	A	8

## Dimensions

