

Pro

26W 25000h BX

The Airam Pro LED range's new high-power LEDs were introduced to replace traditional discharge lamps. By switching to the LED version, it is not only help to save the environment by avoiding the use of lamps that containing mercury and other toxic materials, but also save up to 75% in energy consumption. The lamp's oval-shaped opal cover provides even, energy-efficient illumination. Two different E27-base lamp models are available. Long service life, 25,000 hours. The colour temperature is 4,000 K.

Opal elliptical LED lamp replacing discharge lamp, 26W 4000K E27 4000lm 25000h 90x245mm, cardboard packing. Supply frequency ~50/60Hz.



26W 25000h BX

| PRODUCT CODE | CODE | KG | PRODUCT FAMILY |
|--------------|--------|-----|----------------|
| 4810022 | A8EDAD | 0.2 | Pro |

Mounting

| | |
|---------------------------|------|
| Degree of protection (IP) | IP21 |
|---------------------------|------|

Structure

| | |
|-------------------------|-------|
| Colour | White |
| Housing colour | White |
| Energy efficiency class | D |

Dimming and control

| | |
|----------------------------------|-----|
| Dimming phase cut-off | No |
| Dimming phase cut-on | No |
| Dimming Touch and Dim | No |
| Dimming Zigbee | No |
| Dimming Bluetooth | No |
| Dimming Wi-Fi | No |
| No dimming function | Yes |
| Remote operation possible | No |
| With movement sensor | No |
| With remote control | No |
| With twilight switch | No |
| Compatible with Apple HomeKit | No |
| Compatible with Google Assistant | No |
| Compatible with Amazon Alexa | No |
| IFTTT support available | No |

Photometric data

| | |
|--|------------------------|
| Luminous flux (min) (lm) | 4000 |
| Luminous flux (max) (lm) | 4000 |
| Colour rendering index CRI | 80-89 |
| Colour of light acc. EN 12464-1 | Neutral 3300-5300 K |
| Colour temperature (min) (K) | 4000 |
| Colour temperature (max) (K) | 4000 |
| Beam angle (min) | 360 |
| Beam angle (max) | 360 |
| Colour consistency (McAdam ellipse) | SDCM6 |
| Photobiological safety according to EN 62471 | RG1 |

Lifetime and capacity

Measurements

| | |
|---------------|-----|
| Diameter (mm) | 90 |
| Length (mm) | 245 |

Electrotechnical data

| | |
|----------------------------|-----|
| Nominal voltage (min) (V) | 220 |
| Nominal voltage (max) (V) | 240 |
| Nominal current (min) (mA) | 145 |
| Nominal current (max) (mA) | 145 |
| Power factor | 0.9 |
| Voltage type | AC |
| Total harmonic distortion | 15 |