

## Coring & Stripping

### JCST-QR Series Coaxial Coring & Stripping Tool

- Designed to simultaneously strip the jacket, core the dielectric, strip the aluminum sheath & trim the conductor to the proper length in one quick operation
- Replaceable heat-treated sheath cutting blade produces a smooth, beveled edge
- Standard models feature a "T" handle with a built-in 3/8" drill adapter & ratchet models feature a ratchet "T" handle with a separate 3/8" drill adapter for manual or drill operations
- Durable, all-metal construction



CABLE SIZE	HANDLE	DRILL ADAPTER	MODEL	PART #	CORING BIT KIT MODEL / PART #		JACKET BLADE MODEL / PART #		SHEATH BLADE MODEL / PART #		LENGTH	WEIGHT
320 (7 mm)	Standard "T"	Built-In 3/8" (9.5 mm)	JCST 7MMQR	36515	CB 164K	35148	6667H	19212	CB 60	14902	7.5" (190.5 mm)	1 lb 8 oz (675 g)
	Ratchet "T"	Separate 3/8" (9.5 mm)	JCST 7MMQR-R	36517								
540	Standard "T"	Built-In 3/8" (9.5 mm)	JCST 540QR	36520	CB 143K	33668						
	Ratchet "T"	Separate 3/8" (9.5 mm)	JCST 540QR-R	36523								
715	Standard "T"	Built-In 3/8" (9.5 mm)	JCST 715QR	36525	CB 159K	34664						
	Ratchet "T"	Separate 3/8" (9.5 mm)	JCST 715QR-R	36528								
860	Standard "T"	Built-In 3/8" (9.5 mm)	JCST 860QR	36530	CB 127K	33376						
	Ratchet "T"	Separate 3/8" (9.5 mm)	JCST 860QR-R	36533								

#### Custom JCST-QR Guide

CONNECTOR MANUFACTURER	CABLE SIZE	MODEL	PART #	CORING BIT KIT MODEL / PART #		JACKET BLADE MODEL / PART #		SHEATH BLADE MODEL / PART #		LENGTH	WEIGHT
Commscope® (Trilogy)*	500	JCST 05TI	35103	CB 132K	33752	6667H	19212	CB 60	14902	7.5" (190.5 mm)	1 lb 8 oz (675 g)
	700	JCST 97TI	35109	CB 134K	33762						

### CST MC Series CommScope® MC<sup>2</sup> Cable Coring, Stripping & Chamfering Tool

- Combination tool quickly strips the sheath & cores the dielectric on Commscope® (Trilogy) MC<sup>2</sup> cables in one precise operation
- Durable, all-metal construction with white guide sleeves & double helix coring bit designed for fast & accurate operations on polyethylene disc/air dielectric cable
- Standard models feature a "T" handle with a built-in 3/8" drill adapter & ratchet models feature a ratchet "T" handle with a separate 3/8" drill adapter for manual or drill operations
- Replaceable heat-treated sheath cutting blade produces a smooth, beveled edge



CABLE MANUFACTURER / TYPE	CABLE SIZE	"T" HANDLE	MODEL	PART #	CORING BIT KIT MODEL / PART #		GUIDE SLEEVE COLOR / PART #	BLADE MODEL / PART #		LENGTH	WEIGHT	
CommScope® (Trilogy) MC <sup>2</sup> Cables	500	Standard	CST 500MC	33895	CB 132K	33752	White	33771-2	CB 60	14907	8.38" (213 mm)	1 lb (454 g)
		Ratchet	CST 500MC-R	33796								
	650	Standard	CST 650MC	33900	CB 133K	33757	White	33771-3				
		Ratchet	CST 650MC-R	33797								
	750	Standard	CST 750MC	33905	CB 134K	33762	White	33771-4				
		Ratchet	CST 750MC-R	33798								

### CST 320/7C Series CommScope® QR Cable Coring, Stripping & Chamfering Tool

- Designed to strip the jacket & core the dielectric on MDU 320 Commscope® Quantum Reach (QR) cables
- U.S. Patent No. D515,901S
- Durable, all-metal construction, as well as heat-treated coring bits & easily replaced sheath cutting blades ensure longevity



CABLE COMPATIBILITY		CONNECTOR COMPATIBILITY		MODEL	PART #	CORING BIT KIT MODEL / PART #	REPLACEMENT BLADE MODEL / PART #		CONDUCTOR CLEANING KIT MODEL / PART #		LENGTH	WEIGHT	
MANUFACTURER	TYPE	MANUFACTURER	TYPE				MODEL / PART #	MODEL / PART #	MODEL / PART #	MODEL / PART #			
CommScope®	MDU 320 Quantum Reach (QR)	Corning Gilbert	UltraSeal® QR	CST 320/7C	36760	CB 216	36762	CB 60	14907	CC-320QRF	36766	5" (127 mm)	8 oz (227 g)
			GAF-360-320										
		PCT	DRS 320 QR										
		PPC	EX320 QR										
		Belden	Snap-N-Seal®										