Motion detector

IS 3360 DALI-2 IPD - surface, sq. EAN 4007841 057237







Function description

Higher, further, faster. Infrared motion detector IS 3360 for indoors and out, ideal for watching over high spaces and large areas, such as multi-storey and underground car parks, installation height up to 4 m, 360° angle of coverage, reach 20 m max. (tangential). Available either in round or square surface-mounted and concealed version. DALI-2 Input Device enables sensors to communicate collected sensor data to higher-level lighting management systems.

IS 3360 DALI-2 IPD - surface, sq. EAN 4007841 057237



Technical specifications

Туре	Motion detectors
Dimensions (L x W x H)	95 x 95 x 65 mm
Mains power supply	12 – 22,5 V / 50 – 60 Hz
Sensor Technology	passive infrared
Application, place	Outdoors, Indoors
Application, place, room	production facilities, recreation room, changing room, function room / ancillary room, sports hall, reception / lobby, stairwell, WC / washroom, multi-storey / underground car park, external facade / external area, warehouse, indoors
Installation site	ceiling
Type of installation	Surface wiring
Switching zones	448 switching zones
Electronic scalability	No
Mechanical scalability	No
Mounting height	2,5 – 4,00 m
Optimum mounting height	2,8 m
Detection angle	360 °
Angle of aperture	45 °
Sneak-by guard	Yes
Capability of masking out individual segments	Yes
Reach, radial	Ø 8 m (50 m²)

Reach, presence	Ø 3 m (7 m²)
Twilight setting TEACH	Yes
Twilight setting	2 – 1000 lx
Switching output 1, floating	No
Control output, Dali	Addressable/slave
Basic light level function	Yes
With bus coupling	Yes
With remote control	No
Interconnection	Yes
IP rating	IP54
Material	Plastic
Ambient temperature	-20 – 50 °C
Colour	white
Colour, RAL	9003
Manufacturer's Warranty	5 years
Version	DALI-2 IPD - surface, sq.
PU1, EAN	4007841057237

Accessories

EAN 4007841 009151 Remote control Smart Remote


https://www.steinel.de

Motion detector

IS 3360 DALI-2 IPD - surface, sq. EAN 4007841 057237




Detection Zone



Mögliche Montagehöhe: 2,50 m – 4,00 m Orange: radial Schwarz: tangential

Circuit diagram



Dimension Drawing

