TOXFREE® PLUS 331 ZH RZ1-K (AS+) FR2

LSHF and fire resistant power cable, for emergency circuits.

ACCORDING TO: IEC 60502-1 / UNE 211025

$B2_{ca}$

C_{ca}



APPLICATION

Toxfree® Plus 331 ZH RZ1-K (AS+) is a fire resistant cable, specially designed to ensure the power supply to emergency circuits in the event of fire. During a fire you need critical circuits to work for life safety (signalling lights, fume extractors, acoustic alarms, water pumps, etc) and a secure plant shutdown. For this reason, its use is highly recommended in public places such as: hospitals, tunnels, offices, production plants, laboratories, hotels, etc.

CONSTRUCTION

Conductor
Electrolytic annealed copper, class 5 (flexible) according to EN 60228 and IEC 60228.

Insulation
Mica tape + Cross-linked polyethylene type DIX-3 according to HD 603.
The standard identification of insulated conductors according to HD 308 is the following:

1 x	Natural
2 x	Blue + Brown
3 G	Blue + Brown + Green/Yellow
3 x	Brown + Black + Grey
3 x + 1 x	Brown + Black + Grey + Blue (reduced cross-section)
4 G	Brown + Black + Grey + Green/Yellow
4 x	Brown + Black + Grey + Blue
5 G	Brown + Black + Grey + Blue + Green/Yellow

Outer sheath
Fireproof polyolefin with low smoke and halogen free fumes under fire conditions.
Orange colour.

CHARACTERISTICS

Electrical performance
Low voltage: 0,6/1 kV.

Thermal performance
Maximum conductor temperature: 90°C.
Maximum short-circuit temperature: 250°C (max. 5 s).
Minimum service temperature: -40°C (fixed and protected installations).
Minimum installation and handling temperature: -0°C

Fire performance
Flame non-propagation according to EN 60332-1 / IEC 60332-1.
Fire non-propagation according to EN 60332-3 / IEC 60332-3 and EN 50399.
Fire resistant (PH120) minimum 120 minutes at 840 °C:
According to IEC 60331-2 / EN 50200 for cable diameter ≤ 20 mm.
According to IEC 60331-1 / EN 50362 for cable diameter > 20 mm.
Fire resistant category C (180 minutes at 950°C), W & Z according to BS 6387.
Fire resistant category Rf 1h30 or Rf 1h (according to cross-section) according to NBN S21-300-1.
Reaction to fire CPR: $B2_{ca}$-s1a,d1,a1 or C_{ca}-s1b,d1,a1 according to EN 50575 (see cross-section).
Halogen free according to EN 60754-1 / IEC 60754-1.
Low corrosive gases emission according to EN 60754-2 / IEC 60754-2.
Low smoke emission according to EN 61034 / IEC 61034:
Light transmittance > 60%.

Mechanical performance
Minimum bending radius: 5x cable diameter.
Impact resistance: AG2 Medium severity.
Test impact at -25°C according HD 604-5D.

Environmental performance
Chemical & Oil resistance: acceptable.
UV Resistant according to EN 50618.
Water resistance: AD5 Jets.

Installation conditions
Open Air.
Buried.
In conduit.

STANDARDS / COMPLIANCE

According to
IEC 60502-1 / UNE 211025

Standards and approvals
AENOR / RoHS / CE


CPR (Construction Products Regulation)
$B2_{ca}$-s1a,d1,a1 (according to cross-section) or
C_{ca}-s1b,d1,a1 (according to cross-section)

sales@topcable.com | www.topcable.com
© 2025 Top Cable - Version 19 - 14.05.2025 | Issued DVC

Top Cable reserves the right to carry out any modification to the data sheets whatsoever without giving previous notice. All renders, specifications and particulars of weights, size and dimensions contained in this documentation is indicative only and shall not be binding on Top Cable.

TOXFREE® PLUS 331 ZH
RZ1-K (AS+) FR2

DIMENSIONS & ADMISSIBLE INTENSITIES



Cross-section (mm^2)	Diameter (mm)	Weight (kg/km)	Open air (A) [1]	Buried (A) [2]	Voltage drop (V/A · km) [3]
1 x 2,5	7,4	80	39	35	20,3
1 x 4	7,9	100	53	46	12,6
1 x 6	8,4	125	68	58	8,41
1 x 10	9,4	170	93	77	4,87
1 x 16	10,4	230	124	100	3,08
1 x 25	11,8	315	161	129	1,98
1 x 35	13,0	415	200	155	1,41
1 x 50	14,4	550	242	183	0,984
1 x 70	16,2	745	310	225	0,693
1 x 95	18,0	960	377	270	0,525
1 x 120	20,2	1.205	437	306	0,410
1 x 150	22,1	1.490	504	343	0,328
1 x 185	24,3	1.790	575	387	0,270
1 x 240	26,9	2.320	679	448	0,204
1 x 300	30,0	2.950	783	502	0,163
1 x 400	34,8	3.815	940	592	0,123
1 x 500	38,5	4.865	1.083	670	0,097
1 x 630	43,7	6.385	1.254	762	0,073
2 x 1,5	10,2	150	26	27	33,9
2 x 2,5	10,4	165	36	35	20,3
2 x 4	11,4	215	49	46	12,6
2 x 6	12,3	270	63	58	8,41
2 x 10	14,6	395	86	77	4,87
2 x 16	16,6	550	115	100	3,08
3 G 1,5	11,3	185	26	27	33,9
3 G 2,5	11,6	210	36	35	20,3
3 G 4	12,5	265	49	46	12,6
3 G 6	13,5	340	63	58	8,41
3 G 10	15,3	480	86	77	4,87
3 x 16	17,7	685	115	100	3,08
3 x 25	22,5	1.075	149	129	1,98
3 x 35	25,5	1.425	185	155	1,41
3 x 50	28,3	1.895	225	183	0,984
3 x 70	31,1	2.535	289	225	0,693
3 x 400	74,8	13.750	886	592	0,123
4 G 1,5	12,2	215	26	27	33,9
4 G 2,5	12,4	250	36	35	20,3
4 G 4	13,6	320	49	46	12,6
4 G 6	15,1	420	63	58	8,41

© 2025 Top Cable - Version 19 - 14.05.2025 | Issued DVC

Top Cable reserves the right to carry out any modification to the data sheets whatsoever without giving previous notice. All renders, specifications and particulars of weights, size and dimensions contained in this documentation is indicative only and shall not be binding on Top Cable.

TOXFREE® PLUS 331 ZH
RZ1-K (AS+) FR2

Cross-section (mm^2)	Diameter (mm)	Weight (kg/km)	Open air (A) [1]	Buried (A) [2]	Voltage drop (V/A · km) [3]
4 G 10	17,1	605	86	77	4,87
4 x 16	19,5	860	115	100	3,08
4 x 25	25,0	1.345	149	129	1,98
4 x 35	27,3	1.765	185	155	1,41
4 x 50	31,3	2.395	225	183	0,984
4 x 70	36,2	3.285	289	225	0,693
4 x 95	40,4	4.230	352	270	0,525
4 x 120	46,0	5.390	410	306	0,410
4 x 150	50,6	6.675	473	343	0,328
4 x 185	56,5	8.150	542	387	0,270
4 x 240	62,2	10.465	641	448	0,204
5 G 1,5	13,6	265	26	27	33,9
5 G 2,5	13,8	300	36	35	20,3
5 G 4	15,0	385	49	46	12,6
5 G 6	16,4	500	63	58	8,41
5 G 10	18,6	725	86	77	4,87
5 G 16	21,5	1.045	115	100	3,08
5 G 25	27,2	1.630	149	129	1,98
5 G 35	30,5	2.155	185	155	1,41
5 G 50	35,0	2.945	225	183	0,984
5 G 70	40,2	4.040	289	225	0,693
5 G 95	45,6	5.260	352	270	0,525
5 G 120	51,8	6.650	410	306	0,410
5 G 150	57,4	8.245	473	343	0,328
5 G 185	63,5	10.000	542	387	0,270
5 G 240	68,3	12.780	641	448	0,204

[1] Reference method F for single-core and method E for multicore cables according to IEC 60364-5-52 in open air at 30°C ambient temperature.
[2] Reference method D2 according to IEC 60364-5-52. Directly buried at 0,7 m depth with soil thermal resistivity of 2,5 K·m/W and 20°C of ground temperature.
[3] At maximum conductor temperature and $\cos\varphi=1$.
In all cases are supposed a single-phase circuit.

© 2025 Top Cable - Version 19 - 14.05.2025 | Issued DVC

Top Cable reserves the right to carry out any modification to the data sheets whatsoever without giving previous notice. All renders, specifications and particulars of weights, size and dimensions contained in this documentation is indicative only and shall not be binding on Top Cable.

TOXFREE® PLUS 331 ZH RZ1-K (AS+) FR2

SHORT-CIRCUIT CURRENT-CARRYING CAPACITIES

Time (s)	0,1	0,2	0,3	0,5	1	1,5	2	2,5	3
A/mm²	452	320	261	202	143	117	101	90	83

CORRECTION FACTORS FOR AIR TEMPERATURE

Air T. (°C)	20	25	30	35	40	45	50	55	60
Factor	1,08	1,04	1	0,96	0,91	0,87	0,82	0,76	0,71

CORRECTION FACTORS FOR GROUND TEMPERATURE

Ground T. (°C)	10	15	20	25	30	35	40	45	50
Factor	1,07	1,04	1	0,96	0,93	0,89	0,85	0,80	0,76

CORRECTION FACTORS FOR SOIL THERMAL RESISTIVITY

Moisture degree of soil	Very damp	Slightly damp	Slightly dry	Dry	Very dry
Thermal Resist. (K·m/W)	1	1,5	2	2,5	3
Factor	1,50	1,28	1,12	1	0,90

Other correction factors (for grouping cables, for harmonic currents), that are not in this specification, can be applied. Further information can be found in IEC 60364-5-52.

© 2025 Top Cable - Version 19 - 14.05.2025 | Issued DVC

Top Cable reserves the right to carry out any modification to the data sheets whatsoever without giving previous notice. All renders, specifications and particulars of weights, size and dimensions contained in this documentation is indicative only and shall not be binding on Top Cable.