



Sealtite HFX black:

Robust, halogen-free, very flexible, good flame properties and superior chemical resistant.

Sealtite HFX is a very flexible conduit designed for use in dynamic applications where frequent and erratic movement can take place. During movement and torque stress, the conduit retains its flexibility and integrity even at low operating temperatures, when other conduit's tend to stiffen. The conduit's halogen free, thermoplastic cover displays excellent flame properties and resistance to chemicals. As such, HFX meets the stringent requirements of the rail and subway infrastructure, train signaling, train and metro building, marine, petrochemical and chemical industries as well as the stringent requirements of closed areas like airports, tunnels and subway stations.

Material & Construction:

Construction: Galvanised steel core, square-locked with cord packing, thick smooth thermoplastic cover (Polyurethane). Size 1/4" and from 1.1/2" a fully inter-locked profile will be used.

Cover specifications: Polyurethane, lead-free according to RoHS, sunlight and UV resistant, suitable for outside installation. The cover is resistant against oil and grease.

Special approvals: Flame properties according to NF F 16-101.

Temperature: -55 °C to +105 °C, intermittent up to +125 °C.
Colour: Black.

Classification according NEN-EN-IEC 61386:

Compression resistance: Class 4, Heavy (1250 N).

Impact resistance: Class 4, Heavy (6 J).

Tensile strength: Class 4, Heavy (1000 N).

Protection class: IP 67 (dust-proof, water-tight).



Square locked

**ANACONDA
SEALTITE®**

**CONDUIT
TYPE HFX
BLACK**

Sealtite	Diametre		Bending radius		Standard carton		Small carton		Reels		Weight (Kg/m)
	Size (Inch)	Inside (mm)	Outside (mm)	Static (mm)	Dynamic (mm)	Metre	Article No. Black	Metre	Article No. Black	Metre	
1/4"	6,4	11,5	40	50	30	331.006.1	-	-	-	-	0,2
5/16"	10,1	14,4	50	65	30	331.010.1	10	331.010.3	250	331.010.5	0,2
3/8"	12,6	17,8	60	85	30	331.012.1	10	331.012.3	250	331.012.5	0,3
1/2"	16,0	21,1	75	110	30	331.016.1	10	331.016.3	150	331.016.5	0,4
3/4"	21,0	26,4	90	140	30	331.020.1	10	331.020.3	120	331.020.5	0,6
1"	26,5	33,1	120	170	30	331.026.1	10	331.026.3	90	331.026.5	0,8
1.1/4"	35,1	41,8	135	215	15	331.035.1	-	-	60	331.035.5	1,1
1.1/2"	40,3	47,8	165	250	15	331.040.1	-	-	-	-	1,5
2"	51,6	59,9	210	300	15	331.050.1	-	-	-	-	2,0

* Also available with stainless steel innercore (see chapter 6, type HFI).

The fittings for Sealtite are outlined in chapter 4 (pages 1 till 23).



Size Sealtite	Inch	1/4"	5/16"	3/8"	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"	2 1/2"	3"	4"
Fittings	ISO	M12-M16	M16-M20	M16-M20	M20	M25	M32	M40	M50	M63	M75	M90	M105
	PG	7	9 - 11	11 - 13,5	16	21	29	36	42	48	-	-	-
	NPT	-	-	1/2"	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"	2 1/2"	3"	4"