

for hazardous areas

KX 0202 C



- 0.75-2.5 mm², Cu 3~

- terminal with 2 clamping units per pole
- 5-pole per pole 8 x 0,75-1 mm² r / f, 6 x 1,5 mm² r / f, 4 x 2,5 mm² r / f, 2 x 4 mm² r / f
- Nominal current of the terminal depending on conductor cross section. See instruction manual or www.hensel-electric.de > Products
- for hazardous areas, can be used in Zone 2 and Zone 22
- "weatherproof" resistant to weather influences (UV due to solar radiation, protected against rainwater, temperature resistant, impact resistant, etc.)
- Cable entries can be drilled individually, order AXM separately (see cable entry systems LES)
- Permitted size of the cable entry system: M20
- external brackets for wall fixing included
- colour: black, RAL 9011

rated insulation voltage	U _i = 690 V a.c./d.c.
rated current	13,5 A (2,5 mm ²) 10,6 A (1,5 mm ²)
tightening torque for terminal	0.5 Nm
weight	0,143 kg
degree of protection	IP 66
material	PC (Polycarbonate)
width	93 mm
height	93 mm
depth	62 mm
in accordance with	IEC 60670-22 DIN EN IEC 60079-1 DIN EN IEC 60079-7 DIN EN 60079-31
Explosion protection code	II 3G Ex ec IIC T6 Gc II 3D Ex tc IIIC T85 Dc

Drawings

Dimension drawing

