

for hazardous areas



KX 0404 C

- 1.5-4 mm², Cu 3~

- terminal with 2 clamping units per pole
- 5-pole per pole 8 x 1,5 mm² r / f, 6 x 2,5 mm² r / f, 4 x 4 mm² r / f, 2 x 6 mm² r / f
- Nominal current of the terminal depending on conductor cross section. See instruction manual or www.hensel-electric.de > Products
- for hazardous areas, can be used in Zone 2 and Zone 22
- "weatherproof" resistant to weather influences (UV due to solar radiation, protected against rainwater, temperature resistant, impact resistant, etc.)
- Cable entries can be drilled individually, order AXM separately (see cable entry systems LES)
- Permitted size of the cable entry system: M20 and M25
- external brackets for wall fixing included
- colour: black, RAL 9011

rated insulation voltage	U _i = 690 V a.c./d.c.
rated current	18,4 A (4 mm ²) 13,9 A (2,5 mm ²) 11,5 A (1,5 mm ²)
tightening torque for terminal	0.7 Nm
weight	0,173 kg
degree of protection	IP 66
material	PC (Polycarbonate)
width	104 mm
height	104 mm
depth	70 mm
in accordance with	IEC 60670-22
Explosion protection code	II 3G Ex ec IIC T6 Gc II 3D Ex tc IIIC T85 Dc

Drawings

Dimension drawing

