


for hazardous areas



RX 0610 T

- 0.5-6 mm², Cu

- 10 terminal blocks WT 4
- {je Klemme 2 x 0,5-6 mm² sol / f, detaillierte Klemmenbestückung siehe technischer Anhang DK-Kabelabzweiggkästen}
- Nominal current of the terminal depending on conductor cross section. See instruction manual or www.hensel-electric.de > Products
- terminal blocks, by Wieland
- jumper bars for terminal blocks: make Wieland IVB WKF 4
- terminal marking, neutral
- for hazardous areas, can be used in Zone 2 and Zone 22
- Cable entries can be drilled individually, order AXM separately (see cable entry systems LES)
- "weatherproof" resistant to weather influences (UV due to solar radiation, protected against rainwater, temperature resistant, impact resistant, etc.)
- external brackets for wall fixing included
- colour: black, RAL 9011

rated insulation voltage	U _i = 690 V a.c./d.c.
rated current	12,3 A (6 mm ²) 10,6 A (4 mm ²) 9 A (2,5 mm ²)
tightening torque for terminal	0.5 Nm
weight	0,313 kg
degree of protection	IP 66
material	PC (Polycarbonate)
width	130 mm
height	130 mm
depth	77 mm
in accordance with	IEC 60670-22 DIN EN IEC 60079-1 DIN EN IEC 60079-7 DIN EN 60079-31
Explosion protection code	II 3G Ex ec IIC T6 Gc II 3D Ex tc IIIC T85 Dc

Drawings

Dimension drawing

