



Note: Product images do not represent this product. Actual product may differ from shown images.

Data subject to change without notice. Always confirm the data is correct from the seller.

KSM 225 BB M1

KSM Side operated polycarbonate switches 16A & 25A

- Easy to install
- IP67

- Fully rated Load Break Switch
- Good resistance against UV and many chemicals
- Membrane gasket cable entries as standard with strain relief 2 x 20 mm on the top, 2 x 20 mm on the bottom and 2 x 15 mm on the base
- Possible to install M20 cable glands
- Wall mounting with membrane gaskets
- Wall mounting dimensions: 62,0 x 90,0 mm
- Large cable terminals 1,5 – 16 mm²
- Padlockable handle to OFF-position
- Handle sealable to ON-position
- Enclosure can be sealed to any position
- Available 2, 3, 4P and 3P with auxiliary contact (S)
- Large 1,5 – 16 mm² neutral and earth terminals on 3P switch, earth on 2P and 4P switches

KSM Installation guide video >>

Technical datasheet >>

Accessories



PRODUCT CARD

MORE INFORMATION

PRODUCT DETAILS

SKU	KSM 225 BB M1
Cable Area to Switch Terminal (only Cu) (mm2) / Bolt size	1.5-16
Cable Gland	4 x membrane gasket
Color	Black
EAN	6419410264911
Enclosure	M1
Enclosure Type	Polycarbonate
IP Rating	IP67
Number of Poles	2
Operation	Side-operated
Weight (kg)	0.21



KATKO Oy
Ruosilantie 2
00390 Helsinki, Finland
E-mail: info(at)katko.com
Tel: +358 (0)9 849 600

NEWSLETTER

Email

SEND »

DOWNLOADS →

[Terms & Conditions](#)

[Manage consent](#)