

wall mounting socket outlet - housing dimensions 126x83



| Product description | |
|---------------------------|---|
| BALS-Prd.-Nr | 11956 |
| EAN | 4024941119566 |
| product category | Wall mounting socket outlet Quick-Connect |
| current | 32A |
| number of poles | 4p |
| number of poles | 3P+PE |
| position of earth contact | 6 h |
| voltage | 380 up to 415V |
| frequency | 50 and 60Hz |

| Product description | |
|------------------------|--|
| protection degree | IP44 |
| colour code | red RAL 3000 |
| Colour of appliance | Hinged lid red, Housing bottom grey, Housing top grey, Collar grey |
| connection design | screwless spring terminals as cage clamp with Kontext-contact |
| maximum conductor size | 10,0 qmm |
| cable entry | 1xM25 top, 2xM25 bottom |
| Height | 156mm |
| Width | 83mm |
| Depth | 130mm |
| dimension of enclosure | 126x83 mm (HxW) |
| material of enclosure | Polyamide |
| contact | The contact carrier is made of polyamide, The contacts are brass |

| Additional technical information | |
|----------------------------------|---|
| | The cable entry is one at top open and two at bottom closed |
| | Lower part of housing rotatable by 180° |
| | 4 cut out fixing holes in the lower part of housing |

| Logistics data | |
|----------------|------------------|
| Weight/pcs | 0.361 kg / Piece |

| Logistics data | |
|----------------|---------------|
| Packaging | Bag |
| Content amount | 1 ST |
| EAN | 4024941119566 |
| Length | 130 mm |
| Width | 83 mm |
| Height | 156 mm |
| Weight | 0.362 kg |
| Volume | 1,683.24 ccm |
| Packaging | Carton |
| Content amount | 10 ST |
| EAN | 4024941936170 |
| Length | 330 mm |
| Width | 216 mm |
| Height | 260 mm |
| Weight | 3.836 kg |
| Volume | 17,062.5 ccm |



1 MB 2

| Ampere | 16 | 16 | 32 | 32 | 32 |
|----------------------------|---------|---------|---------|---------|---------|
| Polzahl | 4 | 5 | 3 | 4 | 5 |
| a | 83,0 | 83,0 | 83,0 | 83,0 | 83,0 |
| b | 126,0 | 126,0 | 126,0 | 126,0 | 126,0 |
| c | 153,0 | 155,0 | 155,0 | 155,0 | 155,0 |
| d | 127,0 | 130,0 | 130,0 | 130,0 | 136,0 |
| e | 68,0 | 68,0 | 68,0 | 68,0 | 68,0 |
| f | 11,0 | 11,0 | 11,0 | 11,0 | 11,0 |
| h ø | 5,5 | 5,5 | 5,5 | 5,5 | 5,5 |
| i | 6,5 | 6,5 | 6,5 | 6,5 | 6,5 |
| k ø | 12,0 | 12,0 | 12,0 | 12,0 | 12,0 |
| l | 65,0 | 65,0 | 65,0 | 65,0 | 65,0 |
| m | 80,0 | 80,0 | 80,0 | 80,0 | 80,0 |
| n ø | 10,0 | 10,0 | 10,0 | 10,0 | 10,0 |
| o | M25 | M25 | M25 | M25 | M25 |
| p | 2 x M25 | 2 x M25 | 2 x M25 | 2 x M25 | 2 x M25 |
| Leiter mm ² min | 1,5 | 1,5 | 2,5 | 2,5 | 2,5 |
| Leiter mm ² max | 4 | 4 | 10 | 10 | 10 |