

plug - with TE screw terminals, for harsh applications



| Product description | |
|-------------------------------|-------------------------------------|
| BALS-Prd.-Nr | 2104 |
| EAN | 4024941021043 |
| product category (PG) | TE plug with Multi-Grip cable gland |
| current (A) | 63A |
| number of poles (P99) | 3p |
| number of poles (P) | 2P+PE |
| position of earth contact (H) | 6 h |
| voltage (V) | 200 up to 250V |
| frequency (HZ) | 50 and 60Hz |

| Product description | |
|-----------------------------|----------------------------------------------------------------------------------------------------------|
| protection degree (SA) | IP44 |
| colour code 1 (KF1) | blue RAL 5015 |
| Colour of appliance | Pusher grey, Collar blue, Housing cover grey, Cable gland grey |
| connection design (AT) | screw terminal as box terminal |
| maximum conductor size (LQ) | 16,0 qmm |
| cable entry (KE) | Cable gland |
| Height | 234mm |
| Width | 97mm |
| Depth | 98mm |
| material of enclosure (GM) | Polyamide |
| contact | The contact carrier is made of high temperature resistant material, the contacts are brass nickel plated |

| Additional technical information | |
|----------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| | For cable diameter from 16 up to max. 36 mm, Screwless housing connection, Multi-Grip cable gland with gasket, integrated cable clamp and additional water evacuation openings |

| Logistics data | |
|----------------|------------------|
| Weight/pcs | 0.535 kg / Piece |
| Packaging | Bag |
| Content amount | 1 ST |
| EAN | 4024941021043 |

| Logistics data | |
|----------------|---------------|
| Length | 98 mm |
| Width | 97 mm |
| Height | 234 mm |
| Weight | 0.536 kg |
| Volume | 2,224.404 ccm |
| Packaging | Carton |
| Content amount | 5 ST |
| EAN | 4024941958752 |
| Length | 325 mm |
| Width | 217 mm |
| Height | 210 mm |
| Weight | 2.881 kg |
| Volume | 13,588.4 ccm |



2 MB 158

| Ampere | 63 | 63 | 63 | | | | |
|----------------------------|-------|-------|-------|--|--|--|--|
| Polzahl | 3 | 4 | 5 | | | | |
| a \varnothing | 96,0 | 96,0 | 96,0 | | | | |
| b | 153,0 | 153,0 | 153,0 | | | | |
| c | 233,0 | 233,0 | 233,0 | | | | |
| d | 167,0 | 167,0 | 167,0 | | | | |
| e \varnothing | 36,0 | 36,0 | 36,0 | | | | |
| Leiter mm ² min | 6 | 6 | 6 | | | | |
| Leiter mm ² max | 16 | 16 | 16 | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |