

panel mounting socket outlet, straight - flange 107x100 fixing centers 85x77



Product description	
BALS-Prd.-Nr	1399
EAN	4024941013994
product category (PG)	GT panel mounting socket outlet straight
current (A)	63A
number of poles (P99)	4p
number of poles (P)	3P+PE
position of earth contact (H)	9 h
voltage (V)	200 up to 250V

Product description	
frequency (HZ)	50 and 60Hz
protection degree (SA)	IP67
colour code 1 (KF1)	blue RAL 5015
Colour of appliance	Hinged lid blue, Bayonet ring grey, Enclosure grey
connection design (AT)	screw terminal as box terminal with Kontex-contact
maximum conductor size (LQ)	25.0 qmm
cable entry (KE)	null
Height	114mm
Width	111mm
Depth	133mm
Flange size vertical	107mm
Flange size horizontal	100mm
Drill hole distance vertical	85mm
Drill hole distance horizontal	77mm
material of enclosure (GM)	Polyamide
contact	The contact carrier is made of high temperature resistant material, the contacts are brass nickel plated

Logistics data	
Weight/pcs	0.495 kg / Piece
Packaging	Bag
Content amount	1 ST

Logistics data	
EAN	4024941013994
Length	133 mm
Width	111 mm
Height	114 mm
Weight	0.496 kg
Volume	1,682.982 ccm
Packaging	Carton
Content amount	5 ST
EAN	4024941946476
Length	295 mm
Width	185 mm
Height	215 mm
Weight	2.639 kg
Volume	9,975 ccm

