

Select your language

- German
- English
- Spanish
- French
- Dutch
- Italian
- Polish
- Czech
- Russian
- Norwegian Bokmål

Worldwide English



NH FUSE 100A 500V GG/GL SIZE 02 - Fuse-link, low voltage, 100 A, AC 500 V, 120 kA, NH02, gL/gG, IEC, dual indicator, live gripping lugs



100NHG02B NH FUSE 100A 500V GG/GL SIZE 02

[Overview](#) [Specifications](#) [Resources](#)



100NHG02B NH FUSE 100A 500V GG/GL SIZE 02

Fuse-link, low voltage, 100 A, AC 500 V, 120 kA, NH02, gL/gG, IEC, dual indicator, live gripping lugs
EL-Nummer (Norway) 1664064

Fuse, fuse-link, low voltage, 100 A, AC 500 V, NH02, gL/gG, IEC, dual (combination) indicator system, square-body with knife blade contacts, live gripping lugs, IEC 60269-2 fuse system A, DIN 43620, VDE 0636-2. Breaking capacity 120 kA



-
-

Delivery program

Product range

Fuse
Basic function
Fuse-link
Field of application
low voltage
Rated current [I]
100 A
Rated voltage
AC 500 V
Construction size
NH02
Utilization category
gL/gG
Status indicator
dual indicator
Description
live gripping lugs
Breaking Capacity
120 kA
usable for size/applications
industrial
Standard/Approval
IEC
Shape
square body with knife blade contacts
Standards/Regulations
IEC 60269-2 fuse system A
DIN 43620
VDE 0636-2

Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts /
Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015])
Construction size
Other
Rated current
100 A
Rated voltage
500 V
Voltage type
AC
Rated switching capacity
120 kA
Utilization category
gL/gG (cable protection/equipment protection)
Type of fuse status indicator
Combination fuse status indicator
Insulated metal gripping lugs (IMGL)
No

Product photo



100nhg02b_b
Photo




100nhg02b_c
Photo



[100nhg02b_pkg](#)
Photo




[100nhg02b_r](#)
Photo



[224nhg02b_c](#)
Photo



[224nhg02b_l](#)
Photo



[224nhg02b_r](#)
Photo

Declaration of Conformity

EU

- [Size 02, 500V fuse-links with blade contacts \(NH fuse system\) \(DA-DC-00003486\)](#)
Asset
(PDF)

UK

- [Size 02, 500V fuse-links with blade contacts \(NH fuse system\) \(DA-DC-00004054\)](#)
Asset
(PDF)

Download-Center

- [Download-Center \(this item\)](#)
Eaton EMEA Download-Center - download data for this item
- [Download-Center](#)
Eaton EMEA Download-Center

[Generate data sheet in PDF format](#)

[Generate data sheet in Excel format](#)

[Write a comment](#)

[Imprint](#) [Privacy Policy](#) [Legal Disclaimer](#) [Terms and Conditions](#)

© 2021 by Eaton Industries GmbH