

Select your language

- German
- English
- Spanish
- French
- Dutch
- Italian
- Polish
- Czech
- Russian
- Norwegian Bokmål

Worldwide English



NH FUSE 32AMP 690V SIZE 000 GG MGL - Fuse-link, low voltage, 32 A, AC 690 V, 120 kA, NH000, gL/gG, IEC, dual indicator, live gripping lugs



32NHG000B-690 NH FUSE 32AMP 690V SIZE 000 GG MGL

[Overview](#) [Specifications](#) [Resources](#)



32NHG000B-690 NH FUSE 32AMP 690V SIZE 000 GG MGL

Fuse-link, low voltage, 32 A, AC 690 V, 120 kA, NH000, gL/gG, IEC, dual indicator, live gripping lugs
 EL-Nummer (Norway) 1664102

Fuse, fuse-link, low voltage, 32 A, AC 690 V, NH000, gL/gG, IEC, dual (combination) indicator system, square-body with knife blade contacts, live gripping lugs, IEC 60269-2 fuse system A, DIN 43620, VDE 0636-2. Breaking capacity 120 kA



-
-

Delivery program

Product range

Fuse
Basic function
Fuse-link
Field of application
low voltage
Rated current [I]
32 A
Rated voltage
AC 690 V
Construction size
NH000
Utilization category
gL/gG
Status indicator
dual indicator
Description
live gripping lugs
Breaking Capacity
120 kA
usable for size/applications
industrial
Standard/Approval
IEC
Shape
square body with knife blade contacts
Standards/Regulations
IEC 60269-2 fuse system A
DIN 43620
VDE 0636-2

Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015])
Construction size
NH000
Rated current
32 A
Rated voltage
690 V
Voltage type
AC
Rated switching capacity
120 kA
Utilization category
gL/gG (cable protection/equipment protection)
Type of fuse status indicator
Combination fuse status indicator
Insulated metal gripping lugs (IMGL)
No

Product photo

- □ [100nhg000b_c](#)
Photo



- [100nhg000b_l](#)
Photo

- □ [100nhg000b_r](#)
Photo

- 
32nhg000b-690_bk
Photo

- 
32nhg000b-690_c
Photo

- 
32nhg000b-690_r
Photo

- 
32nhg000b-690_tp
Photo

Declaration of Conformity

EU

- [Size 000, 690V fuse-links with blade contacts \(NH fuse system\) \(DA-DC-00003483\)](#)
Asset
(PDF)


UK

- [Size 000, 690V fuse-links with blade contacts \(NH fuse system\) \(DA-DC-00004045\)](#)
Asset
(PDF)

Download-Center

- [Download-Center \(this item\)](#)
Eaton EMEA Download-Center - download data for this item
- [Download-Center](#)
Eaton EMEA Download-Center

 [Generate data sheet in PDF format](#)

 [Generate data sheet in Excel format](#)

 [Write a comment](#)

[Imprint](#) [Privacy Policy](#) [Legal Disclaimer](#) [Terms and Conditions](#)

© 2021 by Eaton Industries GmbH