

17 PLYSHIELD® EPR Shielding Tape

A 30 mil (0,76mm) EPR self-amalgamating, conducting tape for shielding high voltage splices and terminations. Use for rebuilding strand shield and insulation shields on high voltage splices and for shielding all types of connections. ASTM-D-4388.

SRT Stress Relief Tape

A SRT is a stress relieving, selfamalgamating rubber compound in roll form. It achieves stress relief in reshaping the electrical field by establishing a controlled voltage gradient across the dielectric interface. It provides an efficient method of achieving stress relief for extruded dielectric cable terminations from 5 kV through 35 kV. The necessity of stocking a variety if stress cone sizes is eliminated.

**HIGH
VOLTAGE
TAPE**



**your tape
SINCE 1896**

17 PLYSHIELD® EPR Shielding Tape

Cat.	Dimensions	Packaging	Weight
2104	3/4" x .030" x 15'	50/case B	13 lbs 6 kg
8212	3/4" x .030" x 15'	100/case C	23 lbs 10 kg
2156	1 1/2" x .030" x 15'	50/case C	23 lbs 10 kg
2159	1 1/2" x .030" x 30'	50/case C	40 lbs 18 kg

SRT Stress Relief Tape

Cat.	Dimensions	Packaging	Weight
8438	3/4" x .0040" x 20'	25/case C	13 lbs 6 kg