

PLYFILL

Plyfill is a self-amalgamating low voltage insulating mastic, designed for quick void-free insulation build-up.

Plyfill can be easily molded by hand to conform to irregular shapes and can be used as primary insulation for splices through 5 kV in conjunction with other insulating tapes. Plyfill provides an excellent moisture seal.

10 PLYSEAL® Insulating Mastic

A self-amalgamating, insulating mastic for insulating and sealing all types of overhead and direct buried electrical connections up to 600 Volts. 10 Plyseal has superior adhesion to metals, cable insulations, and jackets with no adverse effect on polymeric conducting shields. For watersealing duct work, cable ends, and all types of splices.

WATERSEAL MASTIC

A self-amalgamating, mechanical grade mastic used for sealing and water-proofing. Excellent adhesion to metals, cable insulations, and jackets. Soft, malleable nature makes Waterseal ideal for molding and conforming to irregular shapes. Use in conjunction with Plymouth's premium tapes for optimum performance.

INSULATING MASTICS



PLYFILL Tape

Cat.	Color	Dimensions	Packaging	Weight
2644	black	11/2" x .0125" x 5'	38mm x 3,2mm x 1,5m	12roll/case B 9 lbs 4 kg

10 PLYSEAL® Insulating Mastic

Cat.	Form	Dimensions	Packaging	Weight
2626	roll	3 3/4" x .125" x 10'	95mm x 3,2mm x 3m	10/case B 31 lbs 14 kg
2627	pad	3 3/4" x .125" x 3 3/4"	95mm x 3,2mm x 95mm	10 pads/EC, 300/box 31 lbs 14 kg
2632	roll	1 1/2" x .125" x 10'	38mm x 3, 2mm x 3m	8 case 1B 11 lbs 5 kg

WATERSEAL MASTIC

Cat.	Form	Dimensions	Packaging	Weight
2856	roll	2 1/2" x .125" x 2'	64mm x 3,2mm x 0,61m	40 roll/case 1B 17 lbs 8 kg