

Flatstifthylser helisolert rullet modell 0,5-6 mm²



- Materiale: messing, fortinnet Cu/Sn, hardloddet hals.
- Isolasjoner av PC og PA har easy-entry, PC og PA er halogenfrie.

Artikler

Areal 0,5-1,5 mm²

Kat.nr.	E-nr.	Cu AWG/MCM	d	L	W	s	For flatstift	Isol.matr.
<u>A1503FLSF5</u>	2018245	20-16	3,4	19,5	5,5	7	2,8x0,5	PA
<u>A1503FLSF8</u>	2018246	20-16	3,4	19,5	5	7	2,8x0,8	PA
<u>A1505FLSF5</u>	2018247	20-16	4,1	19,5	7,2	7	4,8x0,5	PA
<u>A1505FLSF8</u>	2018248	20-16	4,1	19,5	7,2	7	4,8x0,8	PA
<u>A1507FLSF</u>	2018249	20-16	4	21,3	8,8	7	6,3x0,8	PC

s = avisoleringslengde

Areal 1,5-2,5 mm²

Kat.nr.	E-nr.	Cu AWG/MCM	d	L	W	s	For flatstift	Isol.matr.
<u>A2505FLSF5</u>	2018250	16-14	4,5	19,5	7,2	8	4,8x0,5	PA

Kat.nr.	E-nr.	Cu AWG/MCM	d	L	W	s	For flatstift	Isol.matr.
<u>A2505FLSF8</u>	2018251	16-14	3,9	19,5	7	8	4,8x0,8	PA
<u>A2507FLSF</u>	2018252	16-14	4,5	21,3	8,8	8	6,3x0,8	PC

s = avisoleringslengde

Areal 4-6 mm²

Kat.nr.	E-nr.	Cu AWG/MCM	d	L	W	s	For flatstift	Isol.matr.
<u>A4607FLSE</u>	2018253	12-10	5,4	26	9,2	9	6,3x0,8	PA

s = avisoleringslengde