

# Rundstift 0,25-6 mm<sup>2</sup>



- Materiale: messing/Cu, fortinnet Cu/Sn.
- Isolasjoner av PC har easy-entry, PC og PA er halogenfrie.

## Artikler

### Areal 0,25-0,75 mm<sup>2</sup>

Kat.nr.	E-nr.	Cu AWG/MCM	d	L	s	Rundstift	Isol.matr.
<u>A0802HA</u>	2018264	24-20	3,1	26	7	2,0	PA

s = avisoleringslengde

### Areal 0,5-1,5 mm<sup>2</sup>

Kat.nr.	E-nr.	Cu AWG/MCM	d	L	s	Rundstift	Isol.matr.
<u>A1504HA</u>	2018265	20-16	4	22	7	4,0	PC

s = avisoleringslengde

### Areal 1,5-2,5 mm<sup>2</sup>

Kat.nr.	E-nr.	Cu AWG/MCM	d	L	s	Rundstift	Isol.matr.
<u>A2505HA</u>	2018267	16-14	4,3	20,7	8	5,0	PVC

s = avisoleringslengde

## Areal 4-6 mm<sup>2</sup>

	Kat.nr.	E-nr.	Cu AWG/MCM	d	L	s	Rundstift	Isol.matr.
	<u>A4605HA</u>	2000289	12-10	6,6	25,7	9	5,0	PA

s = avisoleringslengde

---