Spesifikasjoner







Eaton EP-505013

Eaton xEnergy Outdoor distribution board BP-VF/DZ, freestanding, sea-water resistant aluminum, powder-coated, 760x600x320 mm (HxWxD), DIN size 0

General specifications	
PRODUCT NAME	Eaton xEnergy Basic empty enclosure
CATALOG NUMBER	EP-505013
EAN	9010653121510
PRODUCT LENGTH/DEPTH	320 mm
PRODUCT HEIGHT	760 mm
PRODUCT WIDTH	600 mm
PRODUCT WEIGHT	10.5 kg
CERTIFICATIONS	CE
MODEL CODE	BP-VF/DZ-600/7-S0

Powering Business Worldwide

Delivery program

MODEL	Corner model
COLOR	Gray Grey

Technical Data - Mechanical

SURFACE FINISHING	Powder coating
MOUNTING METHOD	Wall mounting Detached
MATERIAL	Aluminum
DEGREE OF PROTECTION	IK10 IP44
NUMBER OF CONNECTOR HOLES	0
NUMBER OF COVERS/DOORS	1
NUMBER OF LOCKS	0
PERMISSIBLE LOAD OF THE ENCLOSURE ACCORDING TO IEC 62208 - MAX	1750 N
PERMISSIBLE LOAD OF THE MOUNTING PLATE ACCORDING TO IEC 62208 - MAX	1400 N
INSTALLATION TYPE	Floor standing wall model

Temperature-rise verification as per IEC 60890

THERMAL DISSIPATION (DELTA T = 20 K) ACCORDING TO IEC/TR 60890	367 W

Additional information

FEATURES	EMC-version Pitched roof Pole fastening
FITTED WITH:	Door
RAL-NUMBER	7035
SUITABLE FOR	Outdoor installation

Ressurser

BROSJYRER	eaton-xenergy-basic-light-brochure-br014024-en-us.pdf
INSTALLERINGSINSTRUKSJONER	eaton-xenergy-basic-bp-vf-dz-il0te-zu.pdf
KATALOGER	eaton-distribution-boards-xenergy-basic-catalog-ca014010en-en-us.pdf
SALGMERKNADER	eaton-f3a-flange-flyer-fl019005en-en-us.pdf

PROSJEKTNAVN:	
PROSJEKTNUMMER:	
FORBEREDT AV:	
DATO:	

Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Irland
Eaton.com

© 2026 Eaton. Med enerett.

Følg oss på sosiale medier for å få den nyeste produkt- og supportinformasjonen.