

ENSTO

Branching connector

KE10.1N



Code	KE10.1N
GTIN	6438100330705
Name	Branching connector Al 4x10-35 mm ² / Cu 1.5-25 mm ²
Description	KE10.1N connector can be used for aluminium and copper conductors. Tightening torque is 10 Nm. The connectors are used either inside metal poles or in separate boxes.
Vendor	Ensto Finland Oy

Technical specification

Certificates

Standards:	IEC 61238-1
------------	-------------

Colors

Color:	Blue
--------	------

Dimensions

Length:	58 mm
Height:	37 mm
Conductor size Al:	10 ... 35 mm ²
Conductor size Cu:	1.5 ... 25 mm ²
Conductor diameter:	1.7 ... 9 mm
Weight:	0.04 kg

Electrical values

Highest system voltage:	1 kV
-------------------------	------

Mechanical

Tightening torque:	10 Nm
--------------------	-------

Others

ETIM Class:	EC000306
-------------	----------

ETIM Technical specification

etim

Model:	Branch
Colour insulation:	Blue
Grease filling against corrosion:	Yes
Nominal cross section:	1.5 ... 35 mm ²
Max. number of cores:	1
Interrupt free shifting:	Yes

Packaging

Pallet package

Package size:	5250 pce
Depth:	1200 mm
Width:	800 mm
Height:	890 mm

Default package

Package size:	50 pce
Depth:	225 mm
Width:	220 mm
Height:	125 mm
Weight:	2.3 kg
Volume:	6.1875 l