

SL4/SL7 SIGNAL TOWERS  
171329



Overview



Specifications



Resources

Contact




Photo is representative




Photo is representative

171329

Eaton Moeller® series SL4 Continuous light modul

How to buy




Photo is representative




Photo is representative



## Designed to work together

Discover other Eaton products and accessories built to enhance this product.

---

**171297**

Eaton Moeller® series SL4 Base module;100-mm aluminum tube and foot

---

**171303**

Eaton Moeller® series SL4 Base module;for vertical mounting on one sides

---

**171305**

Eaton Moeller® series SL4 Base module;100 mm aluminum tube

---

**171306**

Eaton Moeller® series SL4 Base module;250 mm aluminum tube

[View more](#)[View less](#)

## GENERAL SPECIFICATIONS

General specifications

&gt;

<b>PRODUCT NAME</b>	Eaton Moeller® series SL4 Continuous light modu
---------------------	---

<b>CATALOG NUMBER</b>	171329
-----------------------	--------

Product specifications

&gt;

<b>MODEL CODE</b>	SL4-L230-Y
-------------------	------------

<b>EAN</b>	4015081678136
------------	---------------

<b>PRODUCT LENGTH/DEPTH</b>	43 mm
-----------------------------	-------

<b>PRODUCT HEIGHT</b>	75 mm
-----------------------	-------

<b>PRODUCT WIDTH</b>	43 mm
----------------------	-------

<b>PRODUCT WEIGHT</b>	0.043 kg
-----------------------	----------

### CERTIFICATIONS

CSA-C22.2 No. 94-91

UL 508

UL

CSA-C22.2 No. 14-10

CE

CSA Class No.: NKCR7

UL File No.: E29184

UL Category Control No.: NKCR

IEC/EN 60947-5-1

UL report applies to both US and Canada

IEC/EN 60529

Certified by UL for use in Canada

## PRODUCT SPECIFICATIONS

<b>PRODUCT CATEGORY</b>	SL signal towers
-------------------------	------------------

<b>ENCLOSURE COLOR</b>	Black
------------------------	-------

<b>RADIATION ANGLE</b>	360 °
------------------------	-------

<b>LEAKAGE CURRENT</b>	0.003 A
------------------------	---------

<b>OUTSIDE DIAMETER</b>	43 mm
-------------------------	-------

<b>LIGHT MODULES</b>	LED
----------------------	-----

<b>RATED OPERATIONAL VOLTAGE (UE) AT AC - MIN</b>	230 V
---	-------

<b>LIGHT TYPE</b>	Continuous light
-------------------	------------------

<b>DEGREE OF PROTECTION</b>	NEMA 4X IP66
-----------------------------	-----------------

<b>OVERVOLTAGE CATEGORY</b>	III
-----------------------------	-----

<b>RATED OPERATIONAL VOLTAGE(UE) AT DC - MIN</b>	0 V
<b>RATED OPERATIONAL VOLTAGE(UE) AT DC - MAX</b>	0 V
<b>AMBIENT OPERATING TEMPERATURE - MAX</b>	60 °C
<b>RATED OPERATIONAL VOLTAGE(UE) AT AC - MAX</b>	240 V
<b>POLLUTION DEGREE</b>	3
<b>CLIMATIC PROOFING</b>	Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30
<b>COLOR</b>	Yellow
<b>RATED IMPULSE WITHSTAND VOLTAGE(UIMP)</b>	4000 V AC
<b>CONNECTION TO SMARTWIRE-DT</b>	No
<b>FUNCTIONS</b>	Continuous light
<b>MATERIAL</b>	Cap: Polycarbonate (PC) Enclosure: Polycarbonate (PC)
<b>LAMP TYPE</b>	LED
<b>LIFESPAN, ELECTRICAL</b>	100,000 h
<b>AMBIENT OPERATING TEMPERATURE - MIN</b>	-30 °C
<b>TYPE</b>	Continuous light module
<b>MOUNTING POSITION</b>	As required
<b>CURRENT CONSUMPTION</b>	0.03 A, at 230/240 V AC
<b>SHOCK RESISTANCE</b>	Mechanical, According to IEC/EN 60068-2-27 15 g, Mechanical, According to IEC/EN 60068-2-27 11 ms
<b>VOLTAGE TYPE</b>	AC
<b>NUMBER OF MODULES</b>	Max. 10 (with base for mounting on both sides) Max. 5 (with standard base)
<b>RATED INSULATION VOLTAGE (UI)</b>	250 V

Brochures

---

Catalogs

---

Certification reports

---

Drawings

---

eCAD model

---

Installation instructions

---

Installation videos

---

mCAD model

---



[Contact me](#)

171329

Eaton is an intelligent power management company dedicated to improving the quality of life and protecting the environment for people everywhere. We are guided by our commitment to do business right, to operate sustainably and to help our customers manage power — today and well into the future. By capitalizing on the global growth trends of electrification and digitalization, we're accelerating the planet's transition to renewable energy and helping to solve the world's most urgent power management challenges.

