

MAIN CIRCUIT TERMINALS FOR 3RA6 INFEED SIDE
SCREW-TYPE MOTOR FEEDER SIDE SPRING-
LOADED



Figure similar

General technical data:		
Protection class IP		IP20

Installation/ mounting/ dimensions:		
Width	mm	45
Height	mm	32
Depth	mm	30

Certificates/ approvals:			
General Product Approval	EMC	Declaration of Conformity	other



[Environmental
Confirmations](#)

[Confirmation](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrymall>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RA6920-3A>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RA6920-3A>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RA6920-3A&lang=en

last modified:

08/04/2017 