

POWER SUPPLY FOR CONSTANT LOAD PRIM 85..265V AC,  
85..300V DC SEC 24V DC +- 5% MOUNTING WIDTH 2WU (WIDTH  
UNIT) SHORT CIRCUIT AND OVERLOAD PROTECTION



| Model                           |                   |
|---------------------------------|-------------------|
| Product brand name              | SENTRON           |
| Product designation             | Power supply unit |
| Design of the transformer       | Power transformer |
| General technical data          |                   |
| Supplied active power / maximum | 8.4 W             |
| Voltage                         |                   |
| Input voltage                   | 265 V             |
| Output voltage                  |                   |
| • _1 / rated value              | 24 V              |
| • _2 / rated value              | 0 V               |
| • _3 / rated value              | 0 V               |
| Dissipation                     |                   |
| Power loss [W]                  |                   |
| • maximum                       | 0 W               |
| Electricity                     |                   |
| Output current                  |                   |

|                    |        |
|--------------------|--------|
| • maximum          | 0.35 A |
| • _1 / rated value | 0.35 A |
| • _2 / rated value | 0 A    |
| • _3 / rated value | 0 A    |

## Suitability

### Suitability for integration

|                                |    |
|--------------------------------|----|
| • surface-mounted installation | No |
| • flush mounting               | No |

## Product details

|                            |    |
|----------------------------|----|
| Product component / switch | No |
|----------------------------|----|

## Product function

|                                       |     |
|---------------------------------------|-----|
| Product function / Thermal protection | Yes |
|---------------------------------------|-----|

## Inputs Outputs

|                                              |     |
|----------------------------------------------|-----|
| Property of the output / Short-circuit proof | Yes |
|----------------------------------------------|-----|

## Mechanical Design

|                                       |       |
|---------------------------------------|-------|
| Height                                | 64 mm |
| Width                                 | 36 mm |
| Length                                | 90 mm |
| Number of width units                 | 2     |
| Mounting type / Side-by-side mounting | Yes   |

|                          |       |
|--------------------------|-------|
| General Product Approval | other |
|--------------------------|-------|

[Confirmation](#)



## Further information

### Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

### Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=4AC2402>

### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/4AC2402>

### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=4AC2402](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=4AC2402)

### CAX-Online-Generator

<http://www.siemens.com/cax>

### Tender specifications

<http://www.siemens.com/specifications>



