

Product sheet



KEOR LEGRAND

Legrand Keor PDU 800VA - German/Italian Input - 8 German/Italian Sockets (backup + surge protected), USB

REF. 310332 | EAN. 3414971529403

> [Visit e-catalogue](#)

Product charateristics

- 8 Full - Protected Output
- 19" Rack Type
- USB Port
- High Efficiency

Les + prod

Installation

- Rack compatible and ultra-easy setup

Usage

- User Friendly LED indicators, Replaceable fuse for overcurrent protection, front easy access to output plugs

Advantages

- Smart LEDs
- Modern Legrand black/white design

Input voltage	160-290 V
Primary frequency	45-65 Hz
Number of phases primary	1
Output voltage	207-253 V
Secondary frequency	49-61 Hz
Output effective power	480 W
Output apparent power	800 VA
Number of phases secondary	1
SNMP	No
Voltage type	AC
Height	440 mm

Construction type	482.6 mm (19 inch) device
Output power factor	0.6
Overall efficiency	98 %
Potential free switch contact	No
Auto shut down function	No
Input connection	C14
Number of output connections C13	8
Number of output connections C19	0
Number of output connections with protective contact CEE 7/3 (type F)	8
Number of output connections fixed connection	0

Width	88 mm
Depth	150 mm
Weight	5.5 kg
Bridging time full load	0 min
Suitable for network-management	No
USV- technology	Offline

Operating / setting temperature	0-40 °C
Storage temperature	0-40 °C
Sound level	40 dB
Terminal marking indication	No
Type of load	Universal and LED Retrofit
With socket outlet	Yes
Contains Batteries and/or Accumulator	Yes

Documentation

TECHNICAL DOCUMENTATION

-  EXB22078_EN.pdf | PDF (4.09Mo)
-  UPS_LGR_0153_GB_AA.pdf | PDF (0.12Mo)
-  LE10625AC.pdf | PDF (1.21Mo)
-  LE11755AA.pdf | PDF (3.91Mo)
-  EXB21082_EN.pdf | PDF (11.02Mo)
-  UPS_LGR_0153_FR_AA.pdf | PDF (0.16Mo)

CATALOGUE PAGE & OTHERS

-  ex223001_0925.pdf | PDF (0.15Mo)