

Basic 2.0 mm Single-mode Patch Cord, LSZH, CPR Dca SMF-28® Ultra OS2, LC UPC Duplex auf SC UPC Duplex

CORNING

Part Number:
F047202G2Z2000

Cable assemblies are a basic component for any network infrastructure projects you may have. The performance of our patch cords and pigtails comply with the optical and mechanical requirements of the industry. They are available in 1- and 2-fibre combinations. Corning's pre-terminated assemblies use only high-quality Corning optical fibres to ensure total performance quality.

Features and Benefits

Global operations

Worldwide manufacturing facilities and end-to-end vertical integration across the entire process ensure reliable supply and mitigate trade barriers or supply disruptions

Flexible design options


Choice of materials for strength elements and fibre properties dependent on application requirements

Superior Performance Testing

Every termination is tested to ensure the highest in network performance

State-Of-The-Art Manufacturing Processes

Corning proprietary manufacturing processes and advanced technology result in unsurpassed product consistency



Basic 2.0 mm Single-mode Patch Cord, LSZH, CPR Dca, SMF-28® Ultra OS2, LC UPC Duplex to SC UPC Duplex

Basic 2.0 mm Single-mode Patch Cord, LSZH, CPR Dca SMF-28® Ultra OS2, LC UPC Duplex auf SC UPC Duplex

CORNING

Specifications

General Specifications

Flame rating	LSZH/FRNC
Fibre category	Single-Mode (OS2) Ultra
Product category	Patch cords
Cable assembly type	Patch cords
Environment	Indoor
Application	LAN, IBN
Cable Type	Zipcord

Standards

Reaction to Fire	Dca
RoHS	Free of hazardous substances according to RoHS 2011/65/EU
Intermateability	IEC 61754

Environmental Conditions

Temperature range, installation	-20 °C to 70 °C
Temperature range, operation	-20 °C to 70 °C
Temperature range, storage	-20 °C to 70 °C

Design

Fibre count	2
Outer jacket material	LSZH/FRNC
Outer jacket colour	Yellow
Polarity	Crossed, TIA-568 Type-B
Fibre Type	Single-mode

Basic 2.0 mm Single-mode Patch Cord, LSZH, CPR Dca SMF-28® Ultra OS2, LC UPC Duplex auf SC UPC Duplex

CORNING

Mechanical Characteristics

Nominal outer diameter	2 mm
Max. tensile strength, short-term	300 N
Max. tensile strength, long-term	150 N
Crush resistance	1000 N/10 cm
Min. bend radius installation	15 mm
Min. bend radius operation	7.5 mm

Specifications - Connector A

Polish	UPC
Insertion loss, max.	0.25 dB
Tensile strength jacketed cable	50 N
Durability	≤ 0.2 dB change, 500 rematings, FOTP-21
Boot colour	Blue / white
Connector type	LC UPC Duplex
Ferrule material	Ceramic
Housing colour	Blue
Housing material	Composite
Boot type	Duplex
Reflectance	≤ -45 dB

Specifications - Connector B

Polish	UPC
Insertion loss, max.	0.25 dB
Tensile strength jacketed cable	50 N
Durability	≤ 0.2 dB change, 1000 rematings, FOTP-21
Boot colour	Blue / white
Connector type	SC UPC Duplex
Ferrule material	Ceramic

Basic 2.0 mm Single-mode Patch Cord, LSZH, CPR
Dca SMF-28® Ultra OS2, LC UPC Duplex auf SC
UPC Duplex



Specifications - Connector B	
Housing colour	Blue
Housing material	Composite
Boot type	Duplex
Reflectance	≤ -45 dB

Dimensions	
Outer diameter	2 mm



Corning Optical Communications GmbH & Co. KG • Leipziger Strasse 121 • 10117 Berlin, Germany
+00 800 2675 4641 • FAX: • www.corning.com/opcomm/emea

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/emea/trademarks. Corning Optical Communications is ISO 9001 and ISO 14001 certified. © 2025 Corning Optical Communications. All rights reserved.