

Current transformer 150/5A 1,0VA C0,2s



Model	
Product brand name	SETRON
Operating apparent output / rated value	1 V·A
Protection class	
Protection class IP	IP20
• Ratio of input current/output current	150/5
• Current / at output / rated value	5 A
• Current / at input / rated value	150 A
Product feature / Touch protection	Yes
Connections	
Type of electrical connection / at output	screw-type terminals
Mechanical Design	
Height	75 mm
Width	60 mm
Depth	55 mm
Mounting type	screw fixing
Net weight	332 g

Environmental conditions

Ambient temperature

- | | |
|------------------------------|--------|
| • during operation / minimum | -30 °C |
| • during operation / maximum | 55 °C |

Certificates

Equipment marking / acc. to DIN EN 61346-2

T

Declaration of Conformity



EG-Konf.

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=4NC5121-2FA21>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/4NC5121-2FA21>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=4NC5121-2FA21

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>